

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>McPherson</u>		<u>SE 1/4 SE 1/4 SW 1/4</u>	<u>24</u>	T <u>19</u> S	R <u>4</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/2 mi. W of McPherson</u>					
2 WATER WELL OWNER: <u>Bob Tatro</u>					
RR#, St. Address, Box # : <u>1300 Eastmoor Dr</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>McPherson, KS 67460</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>158</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>100</u> ft. below land surface measured on mo/day/yr <u>1-21-97</u>			
		Pump test data: Well water was <u>103</u> ft. after <u>2</u> hours pumping <u>15</u> gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>8</u> in. to <u>168</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
☒ PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter <u>5</u> in. to <u>148</u> ft., Dia in. to ft., Dia in. to ft.		7 Fiberglass Threaded			
Casing height above land surface: <u>12</u> in., weight <u>2.29</u> lbs./ft. Wall thickness or gauge No. <u>160</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped ☒ Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>148</u> ft. to <u>158</u> ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>120</u> ft., From ft. to ft.					
From <u>125</u> ft. to <u>168</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>23</u> ft., From <u>120</u> ft. to <u>125</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool ☒ Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>NE</u>		How many feet? <u>100</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	13	Gn Clay			
13	47	Br Clay			
47	118	F-C Sand			
118	141	Gn Clay			
141	145	F Sand			
145	158	C Sand			
158	162	Br Clay			
162	168	F Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-21-97</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>447</u>		This Water Well Record was completed on (mo/day/yr) <u>2-8-97</u>			
under the business name of <u>Miller Drilling</u>		by (signature) <u>Ez Miller</u>			