

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: McPherson		SW 1/4 SW 1/4 SW 1/4		20		T 19 S		R 4 E/W	
Distance and direction from nearest town or city street address of well if located within city?						Lat. 38-22-36.641 N			
661 Highway 56, Conway						Long. 97-47-44.484 W			
2 WATER WELL OWNER: Chevron Pipe Line Company									
RR#, St. Address, Box # : 4800 Fournace Place						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Houston, TX 77401-2324						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 25.5 ft. ELEVATION: 1538.01							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was NA ft. after hours pumping gpm							
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8.25 in. to 25.5 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recovery							
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 2 in. to 5.5 ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 5.5 ft. to 25.5 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 3.5 ft. to 25.5 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete									
Grout intervals: From 0 ft. to 2 ft. From 2 ft. to 3.5 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? SW How many feet? 300 Brine Storage									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 11 Clay,									
11 25.5 Clay, silty, Dark Red w/abnt Lt. Gray mottling									
T-4SR									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction									
and was completed on (mo/day/year) 7/17/2012 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8/23/12									
under the business name of GeoCore, Inc. by (signature) Dale Kottel									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									