

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																											
County: McPherson		SW ¼ SW ¼ SE ¼		20		T 19 S		R 4 E/W																																											
Distance and direction from nearest town or city street address of well if located within city? 1/2 mi. N of Conway, Kansas																																																			
2 WATER WELL OWNER: National Cooperative Refinery Assoc. RR#, St. Address, Box # : 1391 Iron Horse Road City, State, ZIP Code : McPherson, KS 67460 Board of Agriculture, Division of Water Resources Application Number:																																																			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:																																																
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 25 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒																																																
			5 TYPE OF BLANK CASING USED:																																																
			1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 11 ft. to 25 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																
			6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete																																																
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 11 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>0</td> <td>7</td> <td>Clay, w/silt, Dark Yellowish Brown</td> <td>FROM</td> <td>TO</td> <td>PLUGGING INTERVALS</td> </tr> <tr> <td>7</td> <td>11.5</td> <td>Clay, w/silt, Reddish Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>11.5</td> <td>14</td> <td>Silt, tr. clay, tr. sand,</td> <td></td> <td></td> <td></td> </tr> <tr> <td>14</td> <td>15</td> <td>No Recovery,</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>15.5</td> <td>Silt, tr. clay, tr. sand,</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15.5</td> <td>25</td> <td>Clay, w/silt, tr. sand, Yellowish Red</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="height: 100px; vertical-align: bottom; text-align: center;">OW-49S, Abovegrade</td> </tr> </table>										0	7	Clay, w/silt, Dark Yellowish Brown	FROM	TO	PLUGGING INTERVALS	7	11.5	Clay, w/silt, Reddish Brown				11.5	14	Silt, tr. clay, tr. sand,				14	15	No Recovery,				15	15.5	Silt, tr. clay, tr. sand,				15.5	25	Clay, w/silt, tr. sand, Yellowish Red				OW-49S, Abovegrade					
0	7	Clay, w/silt, Dark Yellowish Brown	FROM	TO	PLUGGING INTERVALS																																														
7	11.5	Clay, w/silt, Reddish Brown																																																	
11.5	14	Silt, tr. clay, tr. sand,																																																	
14	15	No Recovery,																																																	
15	15.5	Silt, tr. clay, tr. sand,																																																	
15.5	25	Clay, w/silt, tr. sand, Yellowish Red																																																	
OW-49S, Abovegrade																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/24/2012 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 5/15/12 under the business name of GeoCore, Inc. by (signature) <i>Dale Holt</i>																																																			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																			