1 LOCA	TION OF W	ATER WELL:	Fraction			Section Number	er Townsh	ip Number	Range Nu	umber
	McPher		SW 3		E 1/4	29	T 1	9 s	R 4	E/W
				et address of well if locat	ed within	city?	Lat	. 38.36595	N	
~1200	N & 350	' E of Antelope T	Frail & Kio	wa Rd.			Lor			
2 WATI	ER WELL (OWNER: Williams	Mid-Conti	nent Fractionation	& Stora	ge		16. 37.70347	•••	
		lox# : 1372 7th				0	Board of A	griculture, Divis	ion of Water R	esources
	e, ZIP Code		on, Kansas	67460			Application	-	non or vvalor is	coources
				COMPLETED WELL	42	A []				
WITH CON	AN "X" IN									
- .		11		ndwater Encountered 1						
↑	÷	V		C WATER LEVEL						
'	NM/	L NE L		np test data: Well water						
		' E		f A gpm: Well wate						
Mile M	ļ	₋ B	Bore Hole Dian	neter 8 in. to		42 ft.,			to	ft
- "		EV	VELL WATER	TO BE USED AS: 5	Public wa	ater supply	8 Air condition	oning 11 I	njection well	
		,	1 Domestic	c 3 Feedlot 6	Oil field v	vater supply	9 Dewatering	12 (Other (Specify I	below)
, 1	SW	X SE	2 Irrigation	1 4 Industrial 7	Lawn and	d garden only	10 Monitoring	الصهر		
↓ I	ĺ		Vas a chemic	al/bacteriological sample	submitte	d to Departmer	YesN	o√; If yes,	mo/day/yr sam	nie was
Υ ι		S	submitted			W	ater Well Disinf	ecteu? Yes	No v	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Co	ncrete tile	CASING	JOINTS: Glued	Clamn	ed
ے <u>ا</u> 1 S		3 RMP (SR)		6 Asbestos-Cement		ner (specify bel			ed	
(2)F		4 ABS		7 Fiberglass						
		•	in to	32 ft., Dia						
	-									
				. in., weight						14U
		OR PERFORATION I			7			Asbestos-ceme		
1 S		3 Stainless s		5 Fiberglass		RMP (SR)		Other (specify)		· · · · · · ·
	rass	4 Galvanized		6 Concrete tile		ABS	12	None used (ope	en hole)	
SCREEN	OR PERFO	PRATION OPENINGS		5 Gauze	, ,		8 Saw cut		11 None (oper	n hole)
1 C	continuous			6 Wire w	rapped		9 Drilled hole			
2 L	ouvered sh	utter 4 Key	punched	7 Torch				cify)		
SCREEN-	PERFORA	TED INTERVALS:	From	32 ft. to	42	ft., Fı	rom	ft. f	o	ft.
			From	ft. to		ft., Fı	rom	ft. t	o	ft.
(GRAVEL PA	ACK INTERVALS:	From	3 0 ft. to	42 .		rom	_. ft. t	0	ft.
			From	ft. to		ft., Fr	om	ft. t	o	ft.
6 GROU	TMATERIA	L: 1 Neat cer	ment	2 Cement grout	3 Be	ntonite 4	Other			
Grout Inte	rvals: Fro	om ft	t. to	ft., From 2	8	ft to 30	ft. From		. ft. to	ft
		source of possible co		,			stock pens		andoned water	
	tic tank	4 Lateral		7 Pit privy						
•	er lines	5 Cess po		8 Sewage lagoon			ilizer storage			O141)
							tilizer storage 16 Other (specify below) ecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Ins Direction from well? ESE How m							ny feet? 80			
FROM	TO		LITHOLOGIC	LOG	FROM		119 100ti 80	PLUGGING IN	TERVALS	
0	7	Hydroexcavated			1110111	- , ,		LOCOMO	ILITALO	
7	15	Clay, sl. silty, R		,,,,		-				
						1				
15	20	Clay, Red Brow								
20	30	Clay, Lt. Red B								
30	34			Brown mottled Gray						
34	36	Clay, occ. shale								
36	42	Shale, sl. wthrd.	, Red Brow	n mottled Gray Gr						
						1	X44S, Aboveg	rade		
							,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
						1				
			05055151	ON 71						
				ON: This water well was						- 1
		n (mo/day/year)					ecord is true to			
				, 52 7 This	Water W		. / / .	mo/day/yr) ,. /	{{	
under the	business na	ame of	Ge	oCore, Inc.		by (signa	ture)	ile 16	<i>/</i> '	

WATER WELL RECORD Form WWC-5 KSA 82a-1212