


1 LOCATION OF WATER WELL: County: McPherson		Fraction NE ¼ SE ¼ SW ¼		Section Number 29	Township Number T 19 S	Range Number R 4 E/W																																																																																																
Distance and direction from nearest town or city street address of well if located within city? ~1100' N & 75' W of Antelope Trail & Kiowa Rd.					Lat. 38.365347 Long. -97.786954																																																																																																	
2 WATER WELL OWNER: Williams Mid-Continent Fractionation & Storage RR#, St. Address, Box # : 1372 7th Ave. City, State, ZIP Code : McPherson, Kansas 67460 Board of Agriculture, Division of Water Resources Application Number:																																																																																																						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">  </div>		4 DEPTH OF COMPLETED WELL 149.5 ft ELEVATION: Depth(s) Groundwater Encountered 1. _____ ft 2. _____ ft 3. _____ ft WELL'S STATIC WATER LEVEL 36.19 ft below TOC measured on mo/day/yr 11/28/2012 Pump test data: Well water was NA ft. after _____ hours pumping _____ gpm Est. Yield NA gpm: Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter 6 in. to 150 ft, and _____ in. to _____ ft WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes _____ No <input checked="" type="checkbox"/>																																																																																																				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) _____ Welded _____ Blank casing diameter 2 in. to 139.5 ft, Dia _____ in. to _____ ft, Dia _____ in. to _____ ft Casing height above land surface 30 in., weight _____ lbs./ft. Wall thickness or gauge No. Sch. 80 TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) _____ 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From 139.5 ft to 149.5 ft, From _____ ft to _____ ft From _____ ft to _____ ft, From _____ ft to _____ ft GRAVEL PACK INTERVALS: From 134 ft to 150 ft, From _____ ft to _____ ft From _____ ft to _____ ft, From _____ ft to _____ ft																																																																																																						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____ Grout Intervals: From 0 ft to 3 ft, From 3 ft to 130 ft, From 130 ft to 134 ft What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) _____ Direction from well? WSW How many feet? 165																																																																																																						
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>7</td> <td>Hydroexcavated - No Sample,</td> <td>113</td> <td>118</td> <td>Shale, as above, w/anhydrite at 115 and 117</td> </tr> <tr> <td>7</td> <td>18</td> <td>Clay, Brown to Red Brown</td> <td>118</td> <td>150</td> <td>Shale, Red Brown, Brown and Gray</td> </tr> <tr> <td>18</td> <td>21</td> <td>Shale, v. wthrd., Lt. Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>21</td> <td>22.5</td> <td>Shale, Red Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>22.5</td> <td>24</td> <td>Shale, Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>24</td> <td>32</td> <td>Shale, Red Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>36</td> <td>Shale, Lt. Gray to Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>36</td> <td>43</td> <td>Shale, Red Brown to Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>43</td> <td>46</td> <td>Shale, Lt. Gray w/Red Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>46</td> <td>54</td> <td>Shale, Dark Red Brown w/occ. Gray to Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>54</td> <td>82</td> <td>Shale, Red Brown to Brown w/Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>82</td> <td>85</td> <td>Shale, Gray to Lt. Gray Green</td> <td></td> <td></td> <td></td> </tr> <tr> <td>85</td> <td>97</td> <td>Shale, Red Brown to Brown w/Gray</td> <td></td> <td></td> <td>TH14D, Abovegrade</td> </tr> <tr> <td>97</td> <td>99</td> <td>Shale, w/anhydrite stringer, Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>99</td> <td>113</td> <td>Shale, Red Brown to Brown w/Gray</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	7	Hydroexcavated - No Sample,	113	118	Shale, as above, w/anhydrite at 115 and 117	7	18	Clay, Brown to Red Brown	118	150	Shale, Red Brown, Brown and Gray	18	21	Shale, v. wthrd., Lt. Gray				21	22.5	Shale, Red Brown				22.5	24	Shale, Gray				24	32	Shale, Red Brown				32	36	Shale, Lt. Gray to Gray				36	43	Shale, Red Brown to Brown				43	46	Shale, Lt. Gray w/Red Brown				46	54	Shale, Dark Red Brown w/occ. Gray to Gray				54	82	Shale, Red Brown to Brown w/Gray				82	85	Shale, Gray to Lt. Gray Green				85	97	Shale, Red Brown to Brown w/Gray			TH14D, Abovegrade	97	99	Shale, w/anhydrite stringer, Gray				99	113	Shale, Red Brown to Brown w/Gray			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																																	
0	7	Hydroexcavated - No Sample,	113	118	Shale, as above, w/anhydrite at 115 and 117																																																																																																	
7	18	Clay, Brown to Red Brown	118	150	Shale, Red Brown, Brown and Gray																																																																																																	
18	21	Shale, v. wthrd., Lt. Gray																																																																																																				
21	22.5	Shale, Red Brown																																																																																																				
22.5	24	Shale, Gray																																																																																																				
24	32	Shale, Red Brown																																																																																																				
32	36	Shale, Lt. Gray to Gray																																																																																																				
36	43	Shale, Red Brown to Brown																																																																																																				
43	46	Shale, Lt. Gray w/Red Brown																																																																																																				
46	54	Shale, Dark Red Brown w/occ. Gray to Gray																																																																																																				
54	82	Shale, Red Brown to Brown w/Gray																																																																																																				
82	85	Shale, Gray to Lt. Gray Green																																																																																																				
85	97	Shale, Red Brown to Brown w/Gray			TH14D, Abovegrade																																																																																																	
97	99	Shale, w/anhydrite stringer, Gray																																																																																																				
99	113	Shale, Red Brown to Brown w/Gray																																																																																																				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/28/2012 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/27/12 under the business name of GeoCore, Inc. by (signature) <i>Dan Bell</i>																																																																																																						