

1] LOCATION OF WATER WELL: County: Rice Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 28 Township Number T 19 S Range Number R 7W E/W

Distance and direction from nearest town or city street address of well if located within city? 1/2 S of Mitchell, Kansas

2] WATER WELL OWNER: Delmer Conner RR#, St. Address, Box #: Route 1 City, State, ZIP Code: Lyons, Kansas 67554 Board of Agriculture, Division of Water Resources Application Number: None

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of section box with X in NE] 4] DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: Unknown. WELL'S STATIC WATER LEVEL: 38 ft. below land surface measured on mo/day/yr 10/16/85. Pump test data: Well water was 15 gpm; Well water was 8 in. to 75 ft. and 75 ft. after hours pumping. Bore Hole Diameter: 8 in. to 75 ft. and 75 ft. after hours pumping. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No

5] TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 5.5 ft., Dia in. to in. to in. to in. Casing height above land surface: 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft., From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 75 ft., From ft. to ft., From ft. to ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? East How many feet? 150

Table with columns FROM, TO, LITHOLOGIC LOG. Row 1: 0 TO 20 Clay. Row 2: 20 TO 75 Sand Rock with few Shale Streaks.

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/16/85 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 11/30/85 under the business name of Kelly's Water Well Service by (signature) Dewey Dard. INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.