'	WATER WELL RECORD For FRACTION				orm WV sec	TION NUMBE	(SA 82a-12 R TOWNSH	IP NUMBER	RANGE NUMBER	
<sup>—</sup> Sedgwick	SE	1/4 SV	V 1/4	$\mathbf{SW}$	1/4	19	Т 2	25 S	R 1E	E/W
Distance and direction from nearest town or city st	reet addres:	s of well if locat	ed within cit	•						······································
1/4 mile East of Meridian, No						nter, Kan	isas			~~~
		NTER SO	CHOOL	L USD 2	62			Board of Agric	ulture, Division of Wa	ater Resource
RR#,ST. ADDRESS,BOX #: 132 S. CITY, STATE: Valley		r, Kansas				IP CODE: 6	7147	_		
— <del>разначания по на принада на при</del>		COMPLETE	) WELL:	47		IP CODE: 0	ELEVATION:	Application Numb	per:	
WITH AN "X" IN SECTION BOX:		dwater Enco		•	ff.		LELVATION,	ft.		ft.
	~	IC WATER L		12			IDEACE MEAS	n. URED ON mo/da	av/vr: 3/24/	
NWNE	.20017(1	Pump tes		Well wat		JVV LAIVD OV	ft. after		of pumping @	gpn
	Est. Yield:		om	Well wat			ft, after		of pumping @	gpm
₩ Bor	e Hole Dia	ameter	12 ir	٦.	to 4	<b>47</b> ft	. and	in.	to	ft.
k also I dem I I		TO BE USE		Dealalla ecca		(7 Laura	and garden on	9. Dewaterin	•	
	Domestic rrigation	3. Feedl 4. Indus					nditioning	صلا 10. Monitorin	12. Other (Spe	ecify below
		4. muus al/bacteriologica			ater suppl; Department?	YES	NO		hat mo/day/yr wa	as sample
subr	nitted						Water Well Disi	nfected?	YES N	0
TYPE OF CASING USED:	5. W	rought Iron	7. F	iberglass	9. C	ther (Specif	y below) CA	SING JOINTS: 🤇	Glued	Threaded
1. Steel 3. RPM (SR) 2. PVC 4. ABS	6 As	bestos-Cem	ent 8.0	Concrete ti	le SD	R-26			Welded	Clamped
Blank casing diameter 5 ir		to <b>20</b>	ft.,	Dia.	in.	to	ft.,	Dia. i	n. to	ft.
Casing height above land surface:	12					-				11.
TYPE OF SCREEN OR PERFORATION!		in.,	VV	eight:	2.33	lbs. / ft.	walit	hickness or gaug	e No.: .214	
1. Steel 3. Stainless Steel	5. Fibe		(7. P	VC	9. A	ABS	11. C	ther (specify)		
2. Brass 4. Galvanized	6. Con	crete Tile	8. R	MP (SR)	10. /	Asbestos-Ce	ment 12. N	lone used (open h	nole)	
SCREEN OR PERFORATION OPENINGS	S ARE:									
1. Continuous slot 3. Mill slot	t	5. Gauze	d wrappe	d	7. <b>T</b> o	orch cut	9. <b>D</b> ri	lled holes	11. None ( or	oen hole)
2. Louvered shutter 4. Key pur	nched	6. Wire w	rapped		8. <b>S</b> :	aw cut	10. Ot	her (specify)		
SCREEN - PERFORATION INTERVAL	From	20	) ft.	to	47	ft.,	From	ft.	to	ft.
	From	,	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	20	) ft.	to	47	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat co		2 /	Cement G	rout		3. Bentonite			onite hole plu	
Grout Intervals: From 4		to 20		From	ft		₽ ft.,	From	ft. to	<b>S</b> ft.
What is the nearest source of possible con		n:			0. Livesto				15. Oil well/G	
1. Septic tank 4. Lateral I		7. Pit p	•			•		ticide storage	16. Other (spe	
2. Sewer lines 5. Cess Po	ool		age lagoo		1. Fuel sto	-	14. Aban	don water well	None Ap	
3. Watertight sewer line 6. Seepage	e pit	9. <b>Feed</b>	yard	1	2. Fertilize	er storage	Llove o	annu fant?	rtone rip	parent
Direction from well?  From To L	ITHOL	OGIC LC	G		From	То	TOW I	nany feet? LITHOLO	GICLOG	
0 3 topsoil	IIIIOL	<u>0010 L0</u>	<u> </u>		110111	<del>                                     </del>		LITTIOLO	OIO LOO	
3 12 clay										
12 18 sandy clay										
10   26   6   1	······					<b>-</b>	<u> </u>			
18 26 fine sand						+				
26 41 fine sand										
26 41 fine sand										
26 41 fine sand										
26 41 fine sand										
26 41 fine sand										
26 41 fine sand										

was completed on (mo/day/year) 3/24/2011 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/25/2011

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp