


NW-3

1 LOCATION OF WATER WELL: County: Rice Fraction: NE 1/4 NE 1/4 SE 1/4 Section Number: 31 Township Number: T 19 S Range Number: R 9 E

Distance and direction from nearest town or city street address of well if located within city? 417 Main Street

2 WATER WELL OWNER: Pump Mart RR#, St. Address, Box #: 417 Main Chase, KS 67524 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 29.5 ft. ELEVATION: - ft. Depth(s) Groundwater Encountered: 1. 24 ft. 2. - ft. 3. - ft. WELL'S STATIC WATER LEVEL: 11.76 ft. below land surface measured on mo/day/yr 6/16/98 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm Well water was - ft. after - hours pumping - gpm Bore Hole Diameter: 8.675 in. to - ft., and - in. to - ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well ma-3 Was a chemical/bacteriological sample submitted to Department? Yes - No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes - No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped - 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded - Threaded X 7 Fiberglass Blank casing diameter: 2 in. to 19.5 ft. Dia. - in. to - ft. Dia. - in. to - ft. Casing height above land surface: 0 in. weight 5CH 40 lbs./ft. Wall thickness or gauge No. - TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) - 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) - SCREEN-PERFORATED INTERVALS: From 19.5 ft. to 29.5 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft. GRAVEL PACK INTERVALS: From 18.5 ft. to 29.5 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other - Grout Intervals: 1 From 0 ft. to 16 ft. 2 From 16 ft. to 18.5 ft. From - ft. to - ft. From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 13 Insecticide storage 18 Other (specify below) poss. com. site Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2.5	SOIL FILL MATERIAL			
2.5	23.5	clayey silt			
23.5	29.5	silty sand			
29.5	TD	end of borehole			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/27/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 6/17/98 under the business name of AEI by (signature) Duncan M. Duke

OFFICE USE ONLY
T
R
EW
SEC