

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: McPherson		SE ¼ SE ¼ SE ¼		15		T 20 S		R 1 E	
Distance and direction from nearest town or city street address of well if located within city? 5 Miles South & 1 Mile East of Canton, Ks.									
2 WATER WELL OWNER: Floyd Vogts									
RR#, St. Address, Box # : R.R. #2					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Canton, Ks. 67428					Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 62 ft. ELEVATION:						
			Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 12/26/85						
			Pump test data: Well water was ft. after hours pumping gpm						
			Est. Yield 50-70 gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 8 in. to 62 ft., and in. to ft.						
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded									
Blank casing diameter 5 in. to 52 ft. Dia 2.91 in. to ft. Dia 265 ft.									
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 52 ft. to 62 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 15 ft. to 62 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 5 ft. to 15 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? WEST How many feet? 200 ft									
LITHOLOGIC LOG									
FROM	TO								
0	5	Top Soil							
5	8	Brown Clay							
8	12	Green Clay							
12	17	Green Sandy Clay							
17	28	Fine Sand							
28	47	Fine To Medium Sand							
47	62	Medium Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-26-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 12-27-85 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									