


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County McPherson	Fraction NE 1/4 SW 1/4 SW 1/4	Section number 17	Township number 20S	Range number 1W
2. Distance and direction from nearest town or city: From Galva Mount Ridge Rd., 3E-1N-1/4E North in Field			3. Owner of well: Blackstone Drilling Co, R.R. or street: P.O. Box 1184, McPherson, Kansas City, state, zip code: 67460		
4. Locate with "X" in section below: 			Sketch map: 6 mi North mount ridge 3E, 1N, 1/4E work in field		
5. Type and color of material			From	To	6. Bore hole dia. 6 in. Completion date 9-20-79 Well depth 95 ft.
T.S.			0	3	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
Clay			3	22	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other
Sandy Stretch			22	23	9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 120 lbs./ft. Dia. 3 in. to 0 ft. depth Wall Thickness: inches or Dia. 3 in. to 73 ft. depth gage No. 216
Clay			23	25	10. Screen: Manufacturer's name certain tool Type Screen Dia. 3 Slot/gauze 1/16 Length 20 Set between 75 ft. and 95 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/8 x 1/4
Equis Sand			25	30	11. Static water level: 35 ft. below land surface Date 9-20-79
Equis Sand			30	43	12. Pumping level below land surfaces: 40 ft. after 1 hrs. pumping 25 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 25 g.p.m.
Hard Rock			43	47	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date
Clay			47	68	14. Well head completion: 18 inches above grade Pitless adapter
Equis Sand/clay			68	75	15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
Equis Sand			75	95	16. Nearest source of possible contamination: ft. Direction none Type Well disinfected upon completion? Yes <input type="checkbox"/> No <input type="checkbox"/>
Shale			95		17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)					
18. Elevation:	19. Remarks:				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Rosercrantz-Bemis Ent. Inc., 134 Business 1211 W. 4th. Hutchinson, Kans. Address Mike Rowe Date 9-25-79 Signed Authorized representative				