


1 LOCATION OF WATER WELL: County: McPherson		Fraction NE 1/4 SW 1/4 NE 1/4	Section Number 17	Township Number T 20 S	Range Number R 1 W
Distance and direction from nearest town or city street address of well if located within city? 4 Miles South & 1 1/4 Miles West of Canton, KS					
2 WATER WELL OWNER: Lawrence Bullinger RR#, St. Address, Box #: R.R. 2 City, State, ZIP Code: Canton, KS 67428			Board of Agriculture, Division of Water Resources Application Number: 39,936		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 25 ft. 2. 3. ft. 3. ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 6-3-91. Pump test data: Well water was ft. after hours pumping gpm Est. Yield 250-275 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 75 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 1.6 in. to 35 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight 16.15 lbs./ft. Wall thickness or gauge No. 500 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 35 ft. to 75 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 75 ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: None within 1/4 mile 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) NONE 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 4 Top Soil 4 8 Tan Clay 8 13 Green Clay 13 23 Fine Sands 23 24 Limestone 24 28 White Clay 28 33 Fine Brown Sands 33 34 White Clay 34 35 Limestone 35 50 Fine Sand with small clay layers 50 56 Fine Sand with small clay layers 56 74 Fine light Sands 74 75 Green Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-3-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 7-17-91 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					