

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Rice	NW 1/4 SE 1/4 SW 1/4	11	T 20 S	R 10 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 3 miles north and 3/4 mile east of Raymond

2 WATER WELL OWNER:	Clyde Ricker	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	565 Ave. N	Application Number: 42,036
City, State, ZIP Code :	Raymond, KS 67573	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	135	ft. ELEVATION:	Unknown
	Depth(s) Groundwater Encountered	1	ft. 2	ft. 3
	WELL'S STATIC WATER LEVEL	12	ft. below land surface measured on	5-17-96
	Pump test data: Well water was	not ch'd	ft. after	hours pumping
Est. Yield	unknown	gpm: Well water was	ft. after	hours pumping
Bore Hole Diameter	18	in. to	134	ft., and
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well	
	1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering
	2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well
Was a chemical/bacteriological sample submitted to Department?	Yes	No	X	If yes, mo/day/yr sample was submitted
Water Well Disinfected?	Yes	No	X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	X	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass		Threaded	
Blank casing diameter	10	in. to	84	ft., Dia	in. to
Casing height above land surface	12	in., weight	7,80	lbs./ft. Wall thickness or gauge No.	365
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:	From	84	ft. to	134	ft., From
GRAVEL PACK INTERVALS:	From	20	ft. to	134	ft., From

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	Bentonite Holeplug
Grout Intervals:	From	ft. to	ft., From	ft. to	0 ft. to 20 ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	None known
Direction from well?					How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil			
4	6	Clay, brown			
6	23	Sand, fine			
23	40	Clay, brown			
40	50	Clay, gray			
50	70	Clay, brown with caliche, rock, white			
70	76	Clay, brown			
76	80	Clay, yellow, gray			
80	86	Sandstone with little clay, gray			
86	134	Sandstone, clean, loose			
134		Shale, hard			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) under the business name of Clarke Well & Equipment, Inc. by (signature)
