

1 LOCATION OF WATER WELL: SECTION NUMBER 9 TOWNSHIP NUMBER 20 S RANGE NUMBER 11 E	
COUNTY: BARTON FRACTION: SE 1/4 SW 1/4 SW 1/4 DISTANCE AND DIRECTION FROM NEAREST TOWN OR CITY STREET ADDRESS OF WELL IF LOCATED WITHIN CITY: ELLINWOOD 2 1/4 S 1 1/4 E NORTH SIDE	
2 WATER WELL OWNER: TOM KAT LTD. R.E. SCHEUFLE, ELLINWOOD, KS	
RR#, ST. ADDRESS, BOX #: 250 N. ROCK RD. SUITE 310 Board of Agriculture, Division of Water Resources	
CITY, STATE, ZIP CODE: WICHITA, KS 67218 Application Number: T83-516	
3 LOCATE WELL'S LOCATION WITHIN AN "X" IN SECTION BOX: [Diagram of a section box with NW, NE, SW, SE quadrants]	
4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 930.83 ft.	
WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr	
PUMP TEST DATA: Well water was 16 ft. after 1 hour pumping 1 gpm	
EST. YIELD: 7.718 gpm; Well water was 60 ft. after 1 hour pumping 1 gpm	
BORE HOLE DIAMETER: 7 7/8 in. to 60 ft. and 60 in. to 60 ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 15 Clamped	
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded	
Blank casing diameter: 5 in. to 40 ft. Dia. 2.65 lbs./ft. Wall thickness or gauge No. 2.14	
Casing height above land surface: 12 in. weight 2.65 lbs./ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement	
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched 7 Wire wrapped 9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From 12 ft. to 60 ft.	
GRAVEL PACK INTERVALS: From 12 ft. to 60 ft. From 12 ft. to 60 ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout intervals: From 0 ft. to 10 ft. From 10 ft. to 60 ft.	
What is the nearest source of possible contamination: NONE	
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)	
13 Insecticide storage	
Direction from well? How many feet?	
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG	
0 3 SOIL	
3 8 SANDY CLAY	
8 60 GRAVEL	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-83 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 10-7-83	
under the business name of PRINCE WATER WELL SERV. INC. by (signature) Prince Water Well Serv. Inc.	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.	