

JOCHEMS #1

WATER WELL RECORD

Form WWC-5

KSA 82a-1212


1 LOCATION OF WATER WELL:	Fraction <u>NW 1/4 SE 1/4</u>	Section Number <u>25</u>	Township Number <u>T 20 S</u>	Range Number <u>R 11 E</u>
---------------------------	-------------------------------	--------------------------	-------------------------------	----------------------------

County: BARTONDistance and direction from nearest town or city street address of well if located within city?
ELLINWOOD 5 1/2 E 4 3/4 S WESTSIDE2 WATER WELL OWNER: L.D. DRILLING CO. INC.RR#, St. Address, Box #: RT1 BOX 183BCity, State, ZIP Code: GREAT BEND, KS 67530

Board of Agriculture, Division of Water Resources

Application Number: T82-610

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 32 ft. 2. 14 ft. 3. 11-18-82 ft.WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 11-18-82Pump test data: Well water was 14 ft. after 11-18-82 hours pumping 82 gpmEst. Yield 82 gpm: Well water was 14 ft. after 11-18-82 hours pumping 82 gpmBore Hole Diameter: 7 7/8 in. to 60 ft. and 60 in. to 60 ft.

WELL WATER TO BE USED AS:

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped X

1 Steel 3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC 4 ABS

7 Fiberglass

Threaded

Blank casing diameter 5 in. to 40 ft. Dia 40 in. to 40 ft. Dia 40 in. to 40 ft.Casing height above land surface 12 in. weight 265 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass 4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter 4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft.GRAVEL PACK INTERVALS: From 30 ft. to 60 ft. From 30 ft. to 60 ft. From 30 ft. to 60 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.What is the nearest source of possible contamination: NONE

1 Septic tank 4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines 5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	FINE SAND			
3	10	CLAY			
10	25	SAND			
25	30	CLAY			
30	60	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-18-82 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 11-30-82under the business name of REISER WATER WELL SERV. INC. by (signature) Reiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.