

1 LOCATION OF WATER WELL: County: Barton		Fraction C 1/4 SW 1/4		Section Number 29		Township Number T 20 S		Range Number R 11W E/W	
Distance and direction from nearest town or city street address of well if located within city? 4 1/2 S of Ellinwood, Kansas									
2 WATER WELL OWNER: Loretta Eatinger RR#, St. Address, Box # : 1016 Espanola NE City, State, ZIP Code : Albuquerque, New Mexico 87110 Board of Agriculture, Division of Water Resources Application Number: 37146									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 5/30/84 Pump test data: Well water was 61 ft. after 3 hours pumping 900 gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 120 in. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 <u>Irrigation</u> 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes..... <u>No</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>						
5 TYPE OF BLANK CASING USED: 1 <u>Steel</u> 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>Welded</u> 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) <u>Threaded</u> Blank casing diameter 16 in. to 88 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 40 lbs./ft. Wall thickness or gauge No. 188 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 <u>Steel</u> 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 <u>Brass</u> 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 <u>Key punched</u> 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 88 ft. to 120 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 120 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Middle of field Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 40 Clay 40 58 Sand and Gravel 58 68 Clay 68 120 Sand and Gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/30/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 6/14/84 under the business name of Kellys Water Well Service by (signature) <u>Kelly Goss</u> INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									