


KRUEGER H5

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BARTON		Cell 1/2 SW 3/4 SW 1/4	23	T 20 S	R 12 EW
Distance and direction from nearest town or city street address of well if located within city? ELLINWOOD 4S 13/4 W NORTH SIDE					
2 WATER WELL OWNER: TIN DRILLING CO INC		A-KRUEGER GREATBEND, KS			
RR#, St. Address, Box #: 200 E. FIRST SUITE 500		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: WICHITA KS 67202		Application Number: T82-404			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 17 ft. 2. 30 ft. 3. 55 ft.			
		WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 7-16-82			
		Pump test data: Well water was 7 ft. after 7 hours pumping 7 gpm			
		Est. Yield 7 gpm Well water was 7 ft. after 7 hours pumping 7 gpm			
		Bore Hole Diameter 7 7/8 in. to 7 7/8 ft. and 7 7/8 in. to 7 7/8 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued XY Clamped XY			
1 Steel 3 RMP (SR)		Welded XY			
2 PVC 4 ABS		Threaded XY			
Blank casing diameter 5 in. to 55 ft. Dia 55 in. to 55 ft. Dia 55 in. to 55 ft.					
Casing height above land surface 12 in., weight 265 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) XY					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1/8		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) XY					
SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft. From 55 ft. to 75 ft.					
GRAVEL PACK INTERVALS: From 45 ft. to 75 ft. From 45 ft. to 75 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other XY					
Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.					
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	16	SOIL			
16	20	GRAVEL			
20	30	SANDY CLAY			
30	35	GRAVEL			
35	55	CLAY			
55	75	GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-16-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 359 This Water Well Record was completed on (mo/day/yr) 7-22-82 under the business name of PELSEN WATER WELL SERV. INC. by (signature) Anders G. Pelsen					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

END

SEC.

23

SW 1/4

SE 1/4

SW 1/4