WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
nty: Barton	C ¼ SW ¼ NE ¼	25	T 20 S	R 12W E/W

ance and direction from nearest town or city street address of well if located within city?
3 S, 4½ E of Ellinwood, Kansas

WATER WELL OWNER: B. Yoakum
, St. Address, Box # : 2212 McKinley
State, ZIP Code : Great Bend, Ks.67530

L. D. Drilling
Route 1
Great Bend, Ks.67530

Yoakum No. 2
Board of Agriculture, Division of Water Resources
Application Number: T83-38

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N
NW | NE
X
W | E
SW | SE
S

4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: Unknown
Depth(s) Groundwater Encountered 1 10 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 2/17/83
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield 60 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8 in. to 50 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
k casing diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.
ng height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40
E OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
EEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
EEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 10 ft. to 50 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
ROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
ut Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.
t is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
ction from well? South How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Sandy Clay			
5	50	Sand and Gravel			

RECEIVED
AUG 30 1985
BUREAU OF OIL FIELD & ENVIRONMENTAL GEOLOGY

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) ~~constructed~~ (2) reconstructed, or (3) plugged under my jurisdiction and was pleted on (mo/day/year) 186 and this record is true to the best of my knowledge and belief. Kansas er Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 5/29/83
r the business name of Kelly's Water Well Service by (signature)

TRUCTIONS: Use typewriter or ball point pen, *PLEASE PRESS FIRMLY* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top e copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL NER and retain one for your records.