


1 LOCATION OF WATER WELL: County: Barton		Fraction SE 1/4 SE 1/4 SE 1/4		Section Number 33		Township Number T 20 S		Range Number R 12w E/W	
Distance and direction from nearest town or city street address of well if located within city? 1/4W, 6 1/4S of Dartmouth, KS									
2 WATER WELL OWNER: Craig Fischer RR#, St. Address, Box # : 680 SE 70 Road City, State, ZIP Code : Ellinwood, KS 67526 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 73 ft. ELEVATION: unknown Depth(s) Groundwater Encountered 1 18 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 09/01/04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 40 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)						
5 TYPE OF BLANK CASING USED: 1 Steel 2 <u>PVC</u> 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter 5 in. to 58 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 12 in. weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 <u>RMP (SR)</u> 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 58 ft. to 73 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 27 ft. to 48 ft. From 52 ft. to 73 ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other Grout Intervals: From 0 ft. to 27 ft. From 48 ft. to 52 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) pond Direction from well? West How many feet? 75									
FROM TO LITHOLOGIC LOG					FROM TO PLUGGING INTERVALS				
0 4 top sand									
4 15 clay									
15 24 sand and gravel									
24 35 clay									
35 48 sand and gravel									
48 54 clay									
54 73 sand and gravel									
					RECEIVED				
					OCT 28 2004				
					BUREAU OF WATER				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/01/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 186 . This Water Well Record was completed on (mo/day/yr) 09/02/04 under the business name of Kelly's Water Well Service, Inc. by (signature) <i>Kathryn L Good</i>									