


PARRISH.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: BARTON		Fraction: C 1/4 SW 1/4 SW 1/4	Section Number: 12	Township Number: T 20 S	Range Number: R 13 E 10
Distance and direction from nearest town or city street address of well if located within city? GREAT BEND 1 1/4 S 2 E 7 1/2 S EASTSIDE.					
2 WATER WELL OWNER: BLACKBIRD OIL CO.		H. PARRISH, GREAT BEND, KS			
RR#, St. Address, Box #: BOX 1584		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: GREAT BEND, KS 67530		Application Number: T 84-232			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 25 ft.			
		Depth(s) Groundwater Encountered 1. 21 ft. 2. 25 ft. 3. 5-1-84 ft.			
		WELL'S STATIC WATER LEVEL: 21 ft. below land surface measured on mo/day/yr 5-1-84			
		Pump test data: Well water was 778 gpm. Well water was 60 ft. after 7 hours pumping 778 gpm.			
		Bore Hole Diameter: 778 in. to 60 ft. and 7 in. to 60 ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes 5-1-84 No 5-1-84 If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below) 10 Asbestos-cement	
Blank casing diameter: 5 in. to 40 ft. Dia. 12 in. weight 2.65 lbs./ft. Wall thickness or gauge No. 214				CASING JOINTS: Glued XY Clamped XY Welded XY Threaded XY	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS				11 Other (specify) 11 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1/8 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes				10 Other (specify) 10	
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft.					
GRAVEL PACK INTERVALS: From 21 ft. to 60 ft. From 21 ft. to 60 ft. From 21 ft. to 60 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 40 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft. From 40 ft. to 60 ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines NONE 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard				10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	
Direction from well?				How many feet?	
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	SOIL			
2	14	CLAY			
14	25	SAND & CLAY			
25	60	GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed , or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-1-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 5-10-84 under the business name of NEISER WATER WELL SERV. INC. by (signature) Neiser					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4