

PARRISH #1

WATER WELL RECORD Form WWC-5 KSA 82a-1212

PULLING

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BARTON	2 1/4 SW 1/4 SW 1/4	12	T 20 S	R 13 E

Distance and direction from nearest town or city street address of well if located within city?

GREAT BEND 1 1/2 E 1785 EASTSIDE.

2 WATER WELL OWNER: IMPERIAL EAGLE TO PATTY SIMPSON	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: P.O. BOX 1584	Application Number:
City, State, ZIP Code: GREAT BEND, KS 67530	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 1 ft. 2. 1 ft. 3. 1 ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 11-18-85 Pump test data: Well water was 18 ft. after 1 hours pumping 11-18-85 gpm Est. Yield 18 gpm: Well water was 18 ft. after 1 hours pumping 11-18-85 gpm Bore Hole Diameter 7 1/8 in. to 60 ft. and 60 in. to 60 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 3" BELOW 5" in. to 5" ft., Dia 5" in. to 5" ft., Dia 5" in. to 5" ft.			
Casing height above land surface 3" in., weight 5" lbs./ft. Wall thickness or gauge No. 5"			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 60 ft. to 18 ft., From 18 ft. to 13 ft., From 13 ft. to 3 ft.		
GRAVEL PACK INTERVALS:	From 60 ft. to 18 ft., From 18 ft. to 13 ft., From 13 ft. to 3 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 60 ft. to 18 ft., From 18 ft. to 13 ft., From 13 ft. to 3 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? 1/2			13 Insecticide storage	16 Other (specify below)

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
60	18	RD. GRAVEL	60	18	RD. GRAVEL
18	13	CLAY	18	13	CLAY
13	3	BENTONITE	13	3	BENTONITE
3	0	TOP SOIL	3	0	TOP SOIL

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 11-18-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 11-19-85 under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph Reiser
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.