

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number		
County: Barton		se 1/4 ne 1/4 SW 1/4	22	T 20 S	R 13W E/W		
Distance and direction from nearest town or city? 3 1/2 S Great Bend, Ks.			Street address of well if located within city?				
2 WATER WELL OWNER: Dunne-Gardner Pet. Co							
RR#, St. Address, Box # : 200 W Douglas			Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Wichita, Ks. 67202			Application Number: unknown				
3 DEPTH OF COMPLETED WELL: 80 ft. Bore Hole Diameter: 2 1/8 in. to 80 ft., and in. to ft.							
Well Water to be used as:							
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)		
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Observation well			
Well's static water level: 25 ft. below land surface measured on 5 month 7 day 80 year							
Pump Test Data: Well water was ft. after hours pumping. gpm							
Est. Yield 65 gpm: Well water was ft. after hours pumping. gpm							
4 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)			
2 <u>PVC</u>		4 ABS	7 Fiberglass				
Blank casing dia 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface: 12 in., weight # 2.8 lbs./ft. Wall thickness or gauge No. sch 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)		
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)		
Screen or Perforation Openings Are:							
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes			
			7 Torch cut	10 Other (specify)			
Screen-Perforation Dia 5 in. to ft., Dia in. to ft., Dia in. to ft.							
Screen-Perforated Intervals: From 60 ft. to 80 ft., From ft. to ft., From ft. to ft.							
Gravel Pack Intervals: From 10 ft. to 80 ft., From ft. to ft., From ft. to ft.							
5 GROUT MATERIAL:							
1 Neat cement		2 Cement grout	3 <u>Bentonite</u>	4 Other			
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Cess pool	7 Sewage lagoon	10 Fuel storage	14 Abandoned water well		
2 Sewer lines		5 Seepage pit	8 Feed yard	11 Fertilizer storage	15 Oil well/Gas well		
3 Lateral lines		6 Pit privy	9 Livestock pens	12 Insecticide storage	16 Other (specify below)		
Direction from well nw How many feet 85 ? Water Well Disinfected? Yes No							
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year Pump Installed? Yes No							
If Yes: Pump Manufacturer's name Model No. HP Volts							
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.							
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other							
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 5 month 7 day 80 year							
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186							
This Water Well Record was completed on 5 month 16 day 80 year under the business name of Kellys Waterwell Serv. by (signature) <i>Kelly Price</i>							
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		0	35	Top Soil-Clay			
		35	50	Sand			
		50	80	Sand-Gravel			
ELEVATION: unknown							

Depth(s) Groundwater Encountered 1. **35** ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

180

1/3

180

SEC

180

180

180

180