

1 LOCATION OF WATER WELL: County: Barton		Fraction NW 1/4 SW 1/4 SW 1/4	Section Number 34	Township Number T 20 S	Range Number R 13 E/W
Distance and direction from nearest town or city street address of well if located within city? 6 1/2 south of Great Bend, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Jim Adams Rt. 2- Great Bend, Ks. 67530			
		Board of Agriculture, Division of Water Resources Application Number: 882			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 4-17-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield na gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 10 in. to 55 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well live stock Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes hth No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 5 in. to 35 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 2 in., weight 160# lbs./ft. Wall thickness or gauge No.		6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 35 ft. to 55 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 55 ft. to 20 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug					
Grout Intervals: From 20 ft. to 0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? south		How many feet? 70			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top pipe			
3	17	Brown & gray clay			
17	21	Fine sand			
21	28	Brown & white clay and sand streaks			
28	39	Sand and gravel medium, loose, clean			
39	40 1/2	Brown clay			
40 1/2	55	Sand and gravel clean coarse to medium loose			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 4-26-95 under the business name of Rosencrantz-Bemis by (signature) Fredrick Nelson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					