

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton		DW 1/4 SE 1/4 UE 1/4	3	T 20 S	R 14 EW
Distance and direction from nearest town or city street address of well if located within city? Rt 1 Box 103A, Great Bend, Ks.					
2 WATER WELL OWNER: Great Bend Airport					
RR#, St. Address, Box # : Rt 1 Box 103A			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Great Bend, KS. 56730			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 117' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15.5' ft. below land surface measured on mo/day/yr 10-27-77			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 2 1/2" in. to 25' ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 05 well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X					
Blank casing diameter 2.375 in. to 6' ft. Dia in. to ft. Dia in. to SDR 13 ft.					
Casing height above land surface Flush Mt. in. weight lbs. ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 25' ft. to 6' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 25' ft. to 4' ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4' ft. to 3' ft. From 3' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? South How many feet? 60'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5'5	Dk brn silty clay w/ some sand, few pebbles, moist, firm, earthy odor.			
5'5	8	Lt brn silty sand, dry, no odor, firm, fine grained, clay lens at 6'.			
8	10	Lt brn silty sand to sandy silt, dry, loose, no odor, fine grained.			
10	17	Lt brn fine-coarse sand, dry, well graded, no odor.			
17	20	Blk fine-coarse sand, wet, strong odor, subrounded qtz grains.			
20	25	Brn fine-coarse sand w/ few pebbles & cobbles, wet, mod. odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-27-77 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 11-1-77 under the business name of JB Environmental by (signature) James Baker					

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4