

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County:	Barton	SE 1/4 SE 1/4 NW 1/4	17		T 120 S	R 14W E/W

Distance and direction from nearest town or city street address of well if located within city?

1/4 W of Dundee, Kansas

2	WATER WELL OWNER:	Roland Schmidt	Woodman & Iannitti Oil	Schmidt No. 2
	RR#, St. Address, Box # :	Route 1	104 S. Broadway	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Great Bend, Ks. 67530	Wichita, Ks. 67202	Application Number: Unknown

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: Unknown

Depth(s) Groundwater Encountered 18 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 12/5/83

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 60 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 48 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 <u>Oil field water supply</u>
2 Irrigation	4 Industrial	9 Dewatering
	7 Lawn and garden only	10 Observation well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:		3 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 <u>PVC</u>	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 5 in. to 28 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:		7 <u>PVC</u>	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
			11 Other (specify)
			12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 <u>Saw cut</u>	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 28 ft. to 48 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 10 ft. to 48 ft., From ft. to ft., From ft. to ft.

6] GROUT MATERIAL:		1 <u>Neat cement</u>	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:		From 0 ft. to 10 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:			10 Livestock pens		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 <u>Oil well/Gas well</u>	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)	
Direction from well? <u>South</u>			How many feet? <u>60</u>		

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/5/83. 186 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/30/83 under the business name of Kellys Water Well Service by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

17