

LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: Barton		SW 1/4 SW 1/4 SW 1/4	26	T 20 S	R 14W E/W
Location and direction from nearest town or city? 7 E of Pawnee rock, Kansas		Street address of well if located within city?			
WATER WELL OWNER: Woodman & Iannitti Co.		Board of Agriculture, Division of Water Resources			
#, St. Address, Box #: 1008 Douglas Bldg., 104 S. Broadway		Application Number: Unknown			
City, State, ZIP Code: Wichita, Kansas 67202					
DEPTH OF COMPLETED WELL: 67 ft. Bore Hole Diameter: 8 in. to 67 ft. and in. to ft.					
All Water to be used as:					
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well					
2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)					
All's static water level: 19 ft. below land surface measured on 3 month 19 day 1981 year					
Pump Test Data: Well water was ft. after hours pumping. gpm					
Yield: 60 gpm Well water was ft. after hours pumping. gpm					
TYPE OF BLANK CASING USED:		Casing Joints: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing dia: 5 in. to 47 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface: 12 in. weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
Screen or Perforation Openings Are:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
Screen-Perforation Dia: 5 in. to ft. Dia in. to ft. Dia in. to ft.					
Screen-Perforated Intervals: From 47 ft. to 67 ft. From ft. to ft.					
Travel Pack Intervals: From 10 ft. to 67 ft. From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grouted Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Fuel storage 14 Abandoned water well			
1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 15 Oil well/Gas well					
2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 16 Other (specify below)					
3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines					
Direction from well: South How many feet 60? Water Well Disinfected? Yes No					
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample					
Was submitted month day year: Pump Installed? Yes No					
Yes: Pump Manufacturer's name Model No. HP Volts					
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.					
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was					
Completed on 3 month 19 day 1981 year					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186					
This Water Well Record was completed on April 24 day 1981 year under the business					
Name of Kellys Water Well Service by (signature) Kelly Price					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		LITHOLOGIC LOG			
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 40 clay					
40 67 Sand and gravel					
N					
W					
E					
S					
1 Mile					
ELEVATION: Unknown					
Depth(s) Groundwater Encountered 1 19 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)					
INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

80

R

14

FW

SEC

80

SW 1/4

SW 1/4

SW 1/4