


LOCATION OF WATER WELL: County: Barton	Fraction NW ¼ NW ¼ NE ¼	Section Number 35	Township Number T 20 S	Range Number R 14 E/W
---	----------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

Approx. 6½ miles south and 1½ miles west of Great Bend, KS

WATER WELL OWNER: Russell Weathers	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : Route 1 - Box 176	Application Number: not required
City, State, ZIP Code : Great Bend, KS 67530	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 63 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. 21.75 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 21.75 ft. below land surface measured on mo/day/yr 5-31-83
	Pump test data: Well water was not ck'd ft. after hours pumping gpm
	Est. Yield unknown gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter .9 in. to 63 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter .5 in. to .53 ft. Dia . in. to . ft. Dia . in. to . ft.			
Casing height above land surface .18 in. weight 2.277 lbs./ft. Wall thickness or gauge No. .214			

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped
2 Louvered shutter	4 Key punched	7 Torch cut
		8 RMP (SR)
		9 ABS
		10 Other (specify)
		11 None used (open hole)
		12 None used (open hole)

SCREEN-PERFORATED INTERVALS:	From .53 ft. to .63 ft.	From . ft. to . ft.
	From . ft. to . ft.	From . ft. to . ft.
GRAVEL PACK INTERVALS:	From .40 ft. to .63 ft.	From . ft. to . ft.
Annular fill	From 10 ft. to 36 ft.	From . ft. to . ft.

ROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
ROUT INTERVALS:	From .0 ft. to .10 ft.	From .36 ft. to .40 ft.	From . ft. to . ft.	From . ft. to . ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

Direction from well? Northwest How many feet? 120'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	26	Sandy topsoil & fine sand			
26	29	Clay - yellow			
29	53	Sand & gravel, fine			
53	63	Sand & gravel, fine, medium medium]			
63	66	Sand & gravel, wood, black, sandy clay			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/31/83 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 6-11-83
Under the business name of CLARKE WELL & EQ., INC by (signature)
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

20

R

14

FWD

SEC.

35

NW ¼

NW ¼

NW ¼

NE ¼

NE ¼