

WELL RIG #5 WATER WELL RECORD Form WWC-5 KSA 82a-1212 PLUGGING REPORT

LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER

COUNTY: BANTON FRACTION: NW 1/4 NE 1/4 NW 1/4 SECTION NUMBER: 35 TOWNSHIP NUMBER: T 20 S RANGE NUMBER: R 14 E

DISTANCE AND DIRECTION FROM NEAREST TOWN OR CITY STREET ADDRESS OF WELL IF LOCATED WITHIN CITY:

GREAT BEND 6S 3/4W SOUTH SIDE.

WATER WELL OWNER: Sterling Dilling Co.

R# , ST. ADDRESS, BOX # : 30X129

CITY, STATE, ZIP CODE : Sterling, KS 67579

BOARD OF AGRICULTURE, DIVISION OF WATER RESOURCES

APPLICATION NUMBER: T85-862

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 70 ft. ELEVATION:

DEPTH(S) GROUNDWATER ENCOUNTERED 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 21 ft. below land surface measured on mo/day/yr 10-14-85

PUMP TEST DATA: WELL WATER WAS ft. after hours pumping gpm

EST. YIELD gpm WELL WATER WAS ft. after hours pumping gpm

BORE HOLE DIAMETER: 7 7/8 in. to 70 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

WAS A CHEMICAL/BACTERIOLOGICAL SAMPLE SUBMITTED TO DEPARTMENT? Yes No; If yes, mo/day/yr sample was submitted

WATER WELL DISINFECTED? Yes No

TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

7 Fiberglass Threaded

BLANK CASING DIAMETER 3' BELOW to ft., Dia. in. to ft., Dia. in. to ft.

CASING HEIGHT ABOVE LAND SURFACE in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

GROUT INTERVALS: From 1.3 ft. to 3 ft., From ft. to ft., From ft. to ft.

WHAT IS THE NEAREST SOURCE OF POSSIBLE CONTAMINATION: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

DIRECTION FROM WELL? How many feet?

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

70 21 RD. GRAVEL 7.96 Cu ft.

21 13 CLAY 1.30 Cu ft.

13 3 BENTONITE 1 1/2 SACKS.

3 0 TOP SOIL

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-14-85 and this record is true to the best of my knowledge and belief. Kansas

LATER WELL CONTRACTOR'S LICENSE NO. 389 This Water Well Record was completed on (mo/day/yr) 10-15-85

ORDER THE BUSINESS NAME OF RETSEN WATER WELL SERV. INC. BY (SIGNATURE) Randolph J. Reiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4