

LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NW 1/4 Section Number 2 Township Number T 20 S Range Number R 15 EW

Distance and direction from nearest town or city street address of well if located within city?

PAWNEE ROCK 5/4 ME SOUTHSIDE

WATER WELL OWNER: DOYLE FOLHERTS


R#, St. Address, Box # : 815 MORTON

City, State, ZIP Code : GREAT BEND, KS 67530

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL 88 ft. ELEVATION: 814.82 ft.

Depth(s) Groundwater Encountered 1. 59 ft. 2. 75 ft. 3. 88 ft.

WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 8-14-82

Pump test data: Well water was 29 ft. after 1 hours pumping 65 gpm

Est. Yield 80 gpm Well water was 29 ft. after 1 hours pumping 65 gpm

Bore Hole Diameter 7 1/8 in. to 88 ft., and 88 in. to 88 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

- 1 Steel 3 RMP (SR)
2 PVC 4 ABS

- 5 Wrought iron 8 Concrete tile
6 Asbestos-Cement 9 Other (specify below)
7 Fiberglass

CASING JOINTS: Glued XX Clamped XX
Welded XX
Threaded XX

Blank casing diameter 5 in. to 60 ft., Dia 5 in. to 70 ft., Dia 10.78 in. to 10.78 ft.

Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 21.4

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel 3 Stainless steel
2 Brass 4 Galvanized steel

- 5 Fiberglass 8 RMP (SR)
6 Concrete tile 9 ABS

- 7 PVC 10 Asbestos-cement
11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 3/32

- 1 Continuous slot 3 Mill slot
2 Louvered shutter 4 Key punched

- 5 Gauzed wrapped
6 Wire wrapped
7 Torch cut

- 8 Saw cut 11 None (open hole)
9 Drilled holes
10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 70 ft., From 70 ft. to 88 ft.

From 78 ft. to 88 ft., From 88 ft. to 88 ft.

GRAVEL PACK INTERVALS: From 50 ft. to 70 ft., From 70 ft. to 88 ft.

From 75 ft. to 88 ft., From 88 ft. to 88 ft.

GROUT MATERIAL:

- 1 Neat cement 2 Cement grout 3 Benite 4 Other

Grout intervals: From 30 ft. to 20 ft., From 20 ft. to 88 ft., From 88 ft. to 88 ft.

What is the nearest source of possible contamination: NONE

- 1 Septic tank 4 Lateral lines 7 Pit privy
2 Sewer lines 5 Cess pool 8 Sewage lagoon
3 Watertight sewer lines 6 Seepage pit 9 Feedyard

- 10 Livestock pens 14 Abandoned water well
11 Fuel storage 15 Oil well/Gas well
12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	SOIL			
10	55	SANDY SOIL			
55	70	SAND ROCK			
70	75	CLAY			
75	88	SAND ROCK			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-14-82 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 9-3-82

Under the business name of HELSER WATERS WELL SERV by (signature) R. D. R. R.

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

15

EW

SEC.

2

NE 1/4 NW 1/4 NW 1/4