

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		SW 1/4 NW 1/4 NW 1/4		35		T 20 S		R 15 EW	
Distance and direction from nearest town or city street address of well if located within city? 1/2 north 1 east of Pawnee Rock, Ks.									
2 WATER WELL OWNER:		Roger Unruh							
RR#, St. Address, Box # :		Rt. 1							
City, State, ZIP Code :		Pawnee Rock, Ks.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 6-18-91							
		Depth(s) Groundwater Encountered 1. 17 ft. 2. 32 ft. 3. 6-18-91							
		WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 6-18-91							
		Pump test data: Well water was 28 ft. after 1 1/2 hours pumping 225 gpm							
		Est. Yield gpm: Well water was 28 ft. after 1 1/2 hours pumping 225 gpm							
		Bore Hole Diameter 26 in. to 32 ft. and 32 in. to 32 ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes hth No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 16 in. to 22 ft. Dia 22 in. to 22 ft. Dia 22 in. to 22 ft.									
Casing height above land surface 12 in., weight SDR 32.5 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 22 ft. to 32 ft. From 32 ft. to 32 ft. From 32 ft. to 32 ft.							
GRAVEL PACK INTERVALS:		From 17 ft. to 32 ft. From 32 ft. to 32 ft. From 32 ft. to 32 ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 17 ft. From 17 ft. to 32 ft. From 32 ft. to 32 ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none									
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 2 1/2 top soil									
2 1/2 6 Clay									
6 8 Clay with sand and gravel									
8 30 Sand and gravel									
30 31 Fire clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 8-21-91 under the business name of Rosencrantz-Bemis by (signature) Fredrick Dedson									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									