


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pawnee	NE 1/4 NW 1/4 NW 1/4	30	T 20 S	R 16 E (W)

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1 1/2 miles west and 8 miles north of Larned


2 WATER WELL OWNER: Jamie Kirby	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Route 1 - Box 114	Application Number:
City, State, ZIP Code: Larned, KS 67550	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 99 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 31.20 ft. below land surface measured on mo/day/yr 5-26-05
	Pump test data: Well water was not checked ft. after hours pumping gpm
	Est. Yield unknown gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to 100 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below)
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Stock
	Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes <input checked="" type="checkbox"/> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input checked="" type="checkbox"/>
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
(2) PVC	4 ABS		Threaded
Blank casing diameter 5 in. to 87 ft., Dia			
Casing height above land surface 24 in., weight 2.87 lbs./ft. Wall thickness or gauge No .265			
TYPE OF SCREEN OR PERFORATION MATERIAL:	(7) PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	(3) Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 87 ft. to 97 ft., From			ft.
GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From			ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Bentonite Holeplug
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 20 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None known
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	5	Clay, brown			
5	8	Clay, tan			
8	17	Clay, brown			
17	45	Clay, tan with caliche			
45	53	Clay, brown, sandy			
53	60	Clay, white with caliche			
60	75	Clay, brown			
75	90	Clay, white with caliche			
90	96	Drift gravel, fine to coarse			
96	100	Clay, gray, yellow			
100		Clay, dark gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-26-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 8-27-05 under the business name of Clarke Well & Equipment, Inc. by (signature) 
--