WATER W	ELL RECORD	Form WWO	C- 5	Division of Wate	r Resources App. No	PNWW4022
	ON OF WATER WELL:	Fraction		Section Number	Township No.	Range Number
County: F		14 NE 14 NE 14		35	T 20 S	R 16 □E 🗹 W
	al Address of Well Location;		Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)		
15 1/2 north & 2 1/2 east of Larned, Ks.				Longitude: (in decimal degrees) Elevation:		
				Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: Randy Staggs				Collection Method:		
RR#, Street Address, Box #: 1971 90th. Ave.				GPS unit (Make/Model:)		
City, State, ZIP Code : Larned, Ks. 67550				Digital Map/Photo, Topographic Map, Land Survey		
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m						
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 95						
SECTION BOX: Depth(s) Groundwater Encountered _(1)						
N WELL'S STATIC WATER LEVEL70ft. below land surface measured on mo/day/yr7-2-1.0						
Pump test data: Well water wasft. after hours pumping gpm						
EST. YIELD. NAgpm. Well water wasft. after hours pumping gpm						
W E Bore Hole Diameter 1.0in. to .95ft., andin. toft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes V No						
S If yes, mo/day/yr sample was submitted						
water werr districted: [12] Tes [140						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter .5						
Casing height above land surface. 18 in., Weight SDR 26 lbs./ft., Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)						
SCREEN-PERFORATED INTERVALS: From						
CB	AVEL DACK INTERVALS.	From	o 20	π., From	It. t	.0 IL.
GRAVEL PACK INTERVALS: From						
6 GROUT MATERIAL: Neat cement Cement grout Pentonite Other						
Grout Interva	als: From ft to	ft From 2		ft to 0 ft	From	ft. toft.
Grout Intervals: From						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Direction from well .West Distance from well .15. FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS						
FROM TO		ilC LOG	FROM	TO LITHO. L	OG (cont.) or PLU	GOING INTERVALS
0 19 19 29	Clay					
29 35	Gray shale		-			
35 42	Gray shale & sandston					
42 92	Gray shale w/streaks of Ironated sandstone & s					
92 95	Fire clay	oi iaic				
32 35	i lie day					
					*	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .7-2-10						
Kansas Water Well Contractor's License No134 This Water Well Record was completed on (mo/day/year) .7-19-10						
under the bu	siness name of Rosencrant	z-Bemis		. by (signature)	you al	سول
under the business name of Rosencrantz-Bemis by (signature)						
(white, blue, pi	nk) to Kansas Department of Health	and Environment, Bureau of V	Water, Geolo	gy Section, 1000 SW Ja	ickson St., Suite 420, '	Topeka, Kansas 66612-1367.
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						