WATER WELL RECORD			Form W	WC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:		Fraction		Section Number Township No. Range Number		
	ınty: Pa		1/4 SE 1/4 SE		4 27 T 20 S R 18 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:						
fron	from nearest town or intersection: If at owner's address, check here .				Latitude: (in decimal degrees)	
13	/4 South	n, 4 1/4 West of Ash Valle	ey .		Longitude: (in decimal degrees)	
			•		Elevation:	
2 WA	TER W	ELL OWNER: Kyrle Fr	ootechnor		Datum: WGS 84, NAD 83, NAD 27	
2 WATER WELL OWNER: Kyrle Froetschner RR#, Street Address, Box #: 415 Corse Avenue				Collection Method: GPS unit (Make/Model:)		
C'ty Ct 4 7TD Ct 1					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
	,, -	Lamed,	KS 67550		Est. Accuracy:	
3 LOCATE WELL						
1	H AN "X	" IN 4 DEPTH OF O	COMPLETED WEL	L 170	ft.	
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1)				ft. (2)	
	WELL'S STATIC WATER LEVEL. 97ft.				ft. below land surface measured on mo/day/yr. 8-26-13	
	Pump test data: Well water was				ft. after hours pumping gpm	
EST. YIELD. NAgpm. Well water was				ft. after hours pumping gpm		
w Bore Hole Diameter 10 in. to 170 ft., and in. to ft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Stock Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
	S					
S If yes, mo/day/yr sample was submitted						
		ASING USED: Steel		Other		
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded						
Casing diameter .5 in. to						
Casing height above land surface18						
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)						
SCREEN-PERFORATED INTERVALS: From 179 ft. to 110 ft., From ft. to ft.						
From						
GRAVEL PACK INTERVALS: From 170 ft. to 20 ft., From ft. to ft.						
From						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
	Septic ta		_	Livestock	pens Insecticide storage Other (specify below)	
	Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None						
		m well			e from well	
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0	2	Top soil				
2	53	Yellow shale & limeston	ie			
53	84	Black shale				
84	107	Dark gray shale				
107	132	Tan clay w/ rock streaks	3			
132	149	Sandstone & clay				
149	165	Light gray shale w/ stre	aks			
	1==	of sandstone & coal				
165	170	Gray shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .8-26-13						
Kansas	Water W	ell Contractor's License No	o134 This V	Water Well F	Record was completed on (mo/day/year) 9-6-13	
under the business name of Rosencrantz- Bemis Ent. Inc. by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephon	e 785-296·	5524. Send one copy to WATI	ER WELL OWNER and r	etain one for	your records. I nelude fee of \$5.00 for each constructed well. Vi sit us at	
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						