		WATER	WELL RECORD F	orm vvvvC-5	NOA 82a				
1 LOCATION OF WAT		Fraction	m m	i	tion J umber	Township Num	I	Range Numb	
County: Ma Dh		110 1/4	11e 1/11e	2 1/4	5	1 20	S R	_&	
Distance and direction			dress of well if located	within city?					
331	3/ XV (ra lva	1.0.10						
	NER: (Ja/e)	1_1\1.9h	tingale						
RR#, St. Address, Box	(# : 1515 Y	Box39	1000	•		Board of Agri	culture, Division	of Water Re	esources
City, State, ZIP Code		a, K3.	67443	, , , , , , , , , ,		Application N			
3 LOCATE WELL'S LO	OCATION WITH 4	DEPTH OF CO	OMPLETED WELL	64	. ft. ELEVA	TION:			
AN "X" IN SECTION	De De	pth(s) Groundv	vater Encountered 1,	50	ft. 2	2	. ر ft. 3		ft.
ī I	VE WE	ELL'S STATIC	WATER LEVEL 2	<i>9</i> ft. be	elow land sur	face measured on m	o/day/yr //	-6-	42.
	<u> </u>		test data: Well water						
NW	NE Est	^ '.	gpm: Well water						
			terin. to						
N W			-	Public water		8 Air conditioning	11 Injectio		
F i	'''	1 Domestic	,	Oil field wat		9 Dewatering	•	Specify below	w)
SW	SE	2 Irrigation				10 Monitoring well	,		
		•	acteriological sample su	_	-	\ /			
			acteriological sample su	iomitted to De		•	\ /		was sub-
		tted	- M			ter Well Disinfected?		No	
5 TYPE OF BLANK C			5 Wrought iron	8 Concre		CASING JOINT	•		
1 Steel	3 RMP (SR)		6 Asbestos-Cement	9 Other (specify below	v)	Welded		
2 PVC	4 ABS	5-0	7 Fiberglass		611		Threaded		
Blank casing diameter	in.,		ft., Dia			ft., Dia			
Casing height above la	and surface	٠	in., weight C.lac.	77.10	✓ Ibs./¹	ft. Wall thickness or	gauge No. ' 🔫		
TYPE OF SCREEN O	R PERFORATION M	MATERIAL:		Z PV	2	10 Asbes	tos-cement		
1 Steel	3 Stainless ste	eel	5 Fiberglass	8 RM	P (SR)	11 Other	(specify)		
2 Brass	4 Galvanized	steel	6 Concrete tile	9 ABS	3	12 None	used (open hole	∍)	
SCREEN OR PERFOR	RATION OPENINGS	ARE:	5 Gauzeo	d wrapped		8 Saw cut	11 No	one (open ho	ole)
1 Continuous slo	t 3 Mill s	lot	6 Wire w	rapped		9 Drilled holes			
2 Louvered shutt	ter 4 Key p	ounched	7 Torch o	cut 🗸 🚄		10 Other (specify)			
SCREEN-PERFORATE		From	ft. to	00	, ft Fror	m			
		From	ft. to			m			
GRAVEL PA	CK INTERVALS:		2 ft. to						
divite in	OK HVI EHVALO.	From	ft. to		ft., Fror				ft.
6 GROUT MATERIAL	۱ Neat cem		2 Cement grout	3_Bento		Other			
	~	90	ft., From						
What is the nearest so			11., 110111			tock pens	14 Abandon		
	•		7 Dit priva			•	15 Oil well/0		; II
<u> </u>	1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel storage12 Fertilizer storage		16 Other (specify below)		
2 Sewer lines	5 Cess po		8 Sewage lagoo	on		=	16 Other (s)	pecify below,	,
i -	er lines 6 Seepage	pit	9 Feedyard			ticide storage .			
Direction from well?	-	LITUOLOGIO I		T FROM 1	How mai		COING INTERV	/ALC	
FROM TO		LITHOLOGIC L	_OG	FROM	то	PLUC	GGING INTERV	ALS	
0 20	YEllow	Clay		<u> </u>					
20 00	<u> </u>								
20 35	Sandy			.					
		,							
35 50	Ked + Y	ellow	Clay	1					
	4-24		clay						
50 61	Medi	um So	and						
,									
61 64	Red C	Play							
	, ,								
						· · · · · · · · · · · · · · · · · · ·			
				<u> </u>					
7 CONTRACTOR'S	OR LANDOWNER'S	CERTIFICATION	ON: This water well was	s (1) construc	cted, (2) reco	enstructed, or (3) plug	gged under my	jurisdiction a	and was
completed on (mo/day/		- 42				rd is true to the best			
Water Well Contractor		NO	This Water We				- 1/=5	イショ	3
under the business na	1.2.	46110	Drilling		by (signa		210	andl	4.
•		PI FASE PRESS EI	RMLY and PRINT clearly. Rea	se fill in hlanke i			top three copies to	Kansas Denert	ment
			0-0001. Telephone: 913-296-55					, randad Dopan	