WATER WELL RECORD	Form WV	VC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:	Fraction		Section Number Township No. Range Number	
County: McPherson	1/4 SE 1/4 SE			
Street/Rural Address of Well Location; i			Global Positioning System (GPS) information:	
from nearest town or intersection: If at owner's address, check here .		Latitude: (in decimal degrees)		
5 miles North & 2 miles East of Moundridge		Longitude: (in decimal degrees)		
Corner of Cimarron & 24th		Elevation:		
2 WATER WELL OWNER: Scott Koehn		Datum: WGS 84, NAD 83, NAD 27		
1	4th Ave.		Collection Method: GPS unit (Make/Model:)	
City, State, ZIP Code : Moundridge, KS 67107		Digital Map/Photo, Topographic Map, Land Survey		
City, state, 211 code . Modificatinge, No 0/10/		Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m		
3 LOCATE WELL				
	COMPLETED WELL			
SECTION BOX: Depth(s) Ground	water Encountered	(1)	ft. (2) ft. (3) ft.	
N WELL'S STATI	WELL'S STATIC WATER LEVEL12ft. below land surface measured on mo/day/yr01./21./.2011			
	Pump test data: Well water wasft. after hours pumping			
	NE EST. YIELD.n/agpm. Well water wasft. after hours pumpinggpm			
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)				
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well				
S If yes, mo/day/yr sample was submitted				
1 mile Water well disinfected? \(\mathbb{N} \) Yes \(\subseteq \) No				
water went districted: [23 1 cs] 100				
5 TYPE OF CASING USED: Steel PVC A Other polyethylene				
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter				
Casing diameter37.4 in. to				
Casing height above land surface18				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☒ None (open hole)				
Louvered shutter Key punched Saw cut Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From				
From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Otherx.6. wells.				
			. ft. to ft., From ft. toft.	
What is the nearest source of possible contamination: Septic tank				
☐ Septic tank ☐ Lateral lin ☐ Sewer lines ☐ Cesspool	<u> </u>	Livestock Fuel storage		
☐ Watertight sewer lines ☐ Seepage p		Fertilizer s		
Direction from well			e from well	
FROM TO LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 3 Topsdil				
3 22 Clay, brown				
22 55 Sand w/small clay	layers			
55 100 Shale, green				
100 200 Shale, red & gray				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ★★ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year)1/21/11 and this record is true to the best of my/knowledge and belief.				
Kansas Water Well Contractor's License No138 This Water Well Record was completed on (mg/day/year) 1/31/11				
under the business name of Peterson Irrigation, Inc. by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies				
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212				