


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

NE NESE

sec 1/4 1/4 1/4 No.
Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County NESS	Township name HIGH POINT	Fraction SE 1/4	Section number 33	Town number 20	Range number 22 W
Distance and direction from nearest town or city: 2 1/2 MILES NORTH FROM HANSTON				3 Owner of well: RAY McTADDEN		
Street address of well location if in city:				Address: NESS CITY, KANSAS		
Locate with "X" in section below: N 		Sketch map:		4 Well depth: 134 ft. Date of completion 19-APRIL 76 Well diameter 16 in.		
2 Type and color of material				5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well		
Type and color of material				7 Casing: Material STEEL Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 16 in. Weight 185 lbs./ft. ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
				8 Screen: Manufacturer WABRIEN ENTERPRISES Type PUNCHER Dia. 16 " Slot/gauze 1/4 Length 60 Set between 73 ft. and 133 ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material		
BLACK TOPSOIL				From	To	9 Static water level: 40 ft. below land surface Date 19-APRIL 76
BROWN CLAY				0	3	10 Pumping level below land surfaces: 52 ft. after 10 hrs. pumping 500 g.p.m. 64 ft. after 10 hrs. pumping 125 g.p.m. Estimated maximum yield 2000 g.p.m.
SAND				3	18	11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date
YELLOW CLAY				18	28	12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 12 inches above grade
GOOD SAND				28	30	13 Well grouted? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From ft. to ft.
TAN CLAY				30	52	14 Nearest source of possible contamination: ft. 600 Direction NW Type OIL WELL Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
EXCELLENT SAND + GRAVEL				52	56	15 Pump: Manufacturer's name WESTERN LAND ROLLER Model number 68030 HP 25 Volts 480 Length of drop pipe 110 ft. capacity 850 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
GREY CLAY TURNING BLUE				56	90	16 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. DEAN WATERHOUSE DRILLING Business name License No. Address HANSTON KANSAS Signed Dean Waterhouse Date 20 APR 76 Authorized representative
FAIR SAND - DARK				90	105	
RAINBOW CLAY				105	132	
BROCK 90				132	135	
Alluvium				135		
(use a second sheet if needed)						
16 Remarks: elevation Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley 2179 90 2089						

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5