USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

			$\perp$						l
	< <u>√</u> (T	R	EW	sec	1/4	1/4	1/4	Nο.	
MWA	Visa	N	(Wo For	sas State iter Well bes-Bldg	Cor 74	itrac O	tors)	ealth	

			<b>BC</b>	+1					speka, Kansas ooozo	
	County	Township name Fraction SWNW			Section number			Town number	Ronge number	
1 Location of well: Ness		Franklin SW/4 of NW/4				27		T-20-S	R-23-W	
Distance and directi	ion from negrest town or cit	y: i. east of Ne	ess City	3 Owner	of well:	Fr	ush	er & Frusher		
	Il location if in city:			Addre	ess:	Ne		City, Kansas		
Locate with "X" in section below:  N  Sketch map:							4 V	Vell depth: 253_8 ft. [ Well diameter in.	ate of completion 11-1	3 <b>-</b> 75
	1 1 1							Cable tool Rotary  Hollow rod Jetted	Driven Dug	
x	11					l		Jse: Domestic Public		
w  - +-	-¦¦							☐ Test well ☐ ☐	onditioning Commercial	
	iii						7 (	Casina: Material Meta	feight: above/below	
L	<u> </u>						i	Threaded Welded K	Weight lbs./ft	
	Mile -			Т				16 in. to 253 ft. depth!	)rive shoe? 🗌 Yes 🛚 🕰 No	
2	Тур	e and color of material			From	То	8 :	Screen: W.A. Br	own	
Surface					0	3		Manufacturer	)ia	
Brown c	lay				3	25	:	Slot/gauzeL Set between ft. and	ength	
A-1 san	d and gravel				.25	42		Fittings: Gravel pack 🗶 Yes 🗌 No		A
Brown a	nd blue clay				,42	54	,	Static water level: 47 ft. below land surfac		
Good sand and big flat gravel					54	59	10	Pumping level below land sur	faces:	
Blue and gray shale with rock layers					59	116	<u> </u>	ft. after 2 hrs ft. after ½ hrs Estimated maximum yield 22	pumping 700 g.p.m.	
Tan san	dstone with	25% shale mi	xed		116	135	11	Water sample submitted:		
A-l tan	sandstone			·	135	250.		Yes KNo Dat Well head completion:	8	)2
Gray sh	ale			e de la	250	255		☐ Pitless adapter	Inches above grade	O
	The second of the second of the	The Secretary of the Se				5057		Neat cement Benton	ite	
(111-77-3	1 - 1 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	- Vitate 2 - 1				1.30		Depth: From ft. ta  Nearest source of possible co		1 2 W
		ean Waterhou	****	Ling	7			ft Direction Well disinfected upon compl	Type	8
Groutin	ig will be na	ndled by him		·	<del>- 11 }</del>	<del>)</del> (2)			Not installed	
		11_0_ 12_11414 14_11414			**************************************	- <del></del>		Manufacturer's name Model number	HP Volts	N
								Length of drop pipe Type:	ft. capacity g.m.p.	\
in All	uvium						ı	Submersible  Jet	Turbine Reciprocating	
	(us	e a second sheet if needed)	)					Certrifugal	Other	1
16 Remarks: eleva	tion 2017	a'						Water well contractor's certi This well was drilled under m		1
Topography:	Die ge x 3	i 77						repart is true to the best of m		8
□ніп	7	9' 77 7' 521 1'sat thurby	<i>.</i> .					Business name Address Dodge Cit	License No.	>
Upland 2 / C 2 /							Signed Authorized repres	Date 1-18.	75 8	
I P ∨alley		61.	۰ تا ۱				1			1

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5