

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		NE 1/4 SE 1/4 SW 1/4	20	T 20 S	R 3 E/W
Distance and direction from nearest town or city street address of well if located within city?					
3 miles South and 1/2 mile West of McPherson, KS					
2 WATER WELL OWNER: John Larsen		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 816 Pine Ct.		Application Number: N/A			
City, State, ZIP Code: McPherson, KS 67460					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 68 ft. below land surface measured on mo/day/yr 7/24/97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 15-20 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 120 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
X PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
		7 Fiberglass			
Blank casing diameter 5 in. to 95 ft. Dia		Casing height above land surface 12 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 214			
TYPE OF SCREEN OR PERFORATION MATERIAL:		X PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 95 ft. to 105 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 20 ft. to 105 ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout X Bentonite 4 Other			
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool X Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? East		How many feet? 150			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 2 Topsoil					
2 26 Tan Clay					
26 62 Gray Clay					
62 97 Fine to Medium Sand with small clay layers					
97 100 Tan Clay					
100 105 Fine to Medium Sand					
105 120 Gray Clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/24/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 7/30/97 under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					