


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		1/4 NC 1/4 W2 1/4	9	T 20 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city? Approximately 2 miles south of McPherson					
2 WATER WELL OWNER: Equus Beds GMD #2 RR#, St. Address, Box # : 313 Spruce City, State, ZIP Code : Halstead, KS 67056-1925 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 145 ft. ELEVATION: unknown			
<div style="text-align: center;">N 1 Mile W E S</div> 		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 72.43 ft. below land surface measured on mo/day/yr 12-14-04			
		Pump test data: Well water was not checked ft. after hours pumping gpm			
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6 in. to 145 ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 2 (steel) in. to 7 ft., Dia 2 (PVC) in. to 132 ft., Dia					
Casing height above land surface 36 in., weight 3.65 (steel) .70 (PVC) lbs./ft. Wall thickness or gauge No. 154 (steel) 154 (PVC)					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.					
SCREEN-PERFORATED INTERVALS: From 132 ft. to 142 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 127 ft. to 145 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug					
Grout Intervals: From 29 ft. to 119 ft., From 0 ft. to 29 ft., From 119 ft. to 127 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None known					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil			
4	9	Clay, dark brown			
9	14	Clay, brown			
14	65	Clay, tan, sandy, soft			
65	104	Sand, coarse to fine with gravel, fine			
104	112	Clay, gray, hard			
112	143	Sand, coarse to fine with gravel, fine and streak of clay			
143	145	Clay, reddish brown, hard			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-14-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 12-21-04 under the business name of Clarke Well & Equipment, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					