MATTER WELL DECORD	T YVVVC 5	The state of the s
WATER WELL RECORD 1 LOCATION OF WATER WELL:	Form WWC-5	Division of Water Resources App. No. Section Number Township No. Range Number
County: McPherson	1/4 Su 1/4 Su 1/4 1/W 1/4	T 20 S R 3 DE W
Street/Rural Address of Well Location; from nearest town or intersection: If at 750 Fost of 13th Auc	if unknown, distance & direction	Global Positioning System (GPS) information: Latitude: 38.340336 (in decimal degrees) Longitude: 9.7. (in decimal degrees) Elevation:
Hiowalka Lane 2 WATER WELL OWNER: Notional, Cooperative Refinely Collection Method: Bievation: Datum: D WGS 84, D NAD 83, D NAD 27 Collection Method:		
RR#, Street Address, Box #: #356	south Main south Main	Collection Method: ☐ GPS unit (Make/Model:) ☑ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
1 2 TOCATE WART		
WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1) 10 ft. (2) 3.7 ft. (3) ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr. Pump test data: Well water was ft after hours pumping gpm EST. YIELD gpm. Well water was ft after hours pumping gpm Bore Hole Diameter in to ft., and in to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 4 in. to 18 ft., Diameter in. to ft. Casing height above land surface 1 Weight 2.60 lbs./ft., Wall thickness or gauge No. 265.40 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to 128 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 27 ft. to 26 ft., From ft. to ft. From 76 ft. to 7.6 ft., From ft. to ft. From 76 ft. to 7.7 ft. to ft. From 76 ft. to 7.8 ft. From 76 ft. From 76 ft. From ft. Fro		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other		
Grout Intervals: From	ft., From famination: les Pit privy Livestock po Sewage lagoon Fuel storage lit Feedyard Fertilizer sto	t. to
FROM TO LITHOLOG		TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 45 S. tx Cl-x		
45 8 Sand		
86 87 0147		
\$7 130 @ Sand Wicky		
1		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 9.16.11		
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html . KSA 82a-1212		