USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Lacation of well:  | County Scott County | 1/4 C 1/4 ST     | <b>7</b> 1/4 | Section num |    | Township number 20  | Range number  | ₽ <b>⊘</b>           |
|---|---------------------|------------------|--------------|-------------|----|---|---|----------------------|
| 2. Distance and direction from nearest town or city: North on 83 to  Scott County line, 2½ North, ½ East  Street address of well location if in city:  City, state, zip code: |                     |                  |              |             |    | Fairleigh Corporation<br>Scott City, KS 67841                           |   |                      |
| 4. Locate with "X" in section below: Sketch map:  |                     |                  |              |             |    | 6. Bore hole dia. 26 in. Completion date D 30 Well depth 170 ft.        |   |                      |
| NW  | <br>  NE            |                  |              |             |    | 7 Cable tool Rotary<br>Hollow rod Jetted                                |   | se rotary            |
| * W   1   | E E                 |                  |              |             |    | 8. Use: Domestic Pu  X   Irrigation Ai  Lown Oi                         | blic supply Ind<br>r conditioning Sto<br>I field water Ot | ck                   |
| SW  | SE<br>I             |                  |              |             |    | 9. Casing: Material <b>Stee</b> Threaded Welded X  RMP PVC              | Height: Above or be                                       | elow<br>in.          |
| 1 Mi  |                     |                  |              |             |    | Dio 16 in. to 170 ft. depi  |   | _lbs./ft. <br>hes.or |
| 5. Type and color of  | material            |                  |              | From        | То | Dia in. to ft. dept  10. Screen: Manufacturer's n                       | h gage No219  |                      |
|   |                     |                  |              |             |    | Type Johnson Galves Slot/gauze Q=130 Pla                                |   | Screen               |
|   |                     |                  |              |             |    | Set between <b>160-170</b> ft. o  | Peni  | ft .                 |
|   |                     |                  |              |             |    | Gravel pack? Yes Size rar   | mo./  | /day/yr.             |
|   |                     |                  |              |             |    | 12. Pumping level below land surf                                       | surfaces:   |                      |
| ***   |                     |                  |              |             |    |   |   |                      |
|   |                     |                  |              |             |    | 13. Water sample submitted: Yes X No [                                  | mo./<br>Date  | day/yr.              |
|   |                     |                  |              |             |    | 14. Well head completion: Pitless adapter 1 ft.                         | Inches above g  | rade                 |
|   |                     |                  |              |             |    | 15. Well grouted? <b>Yes</b> With: Neat cement  Depth: From ft. to _    |   | oncrete              |
|   |                     |                  |              |             |    | 16. Nearest source of possible ft Direction                             |   |                      |
| ,   |                     |                  | ,            |             |    | Well disinfected upon completed 17. Pump:                               | Not installed   | No                   |
|   |                     |                  |              |             |    | Manufacturer's name <b>Gottle</b> Model number  Length of drop pipe 160 | HP 40 Volte  - ft. capacity 500                           |                      |
|   |                     |                  |              |             |    | Type: Submersible   | X Turbine   |                      |
|   | (Use a second       | sheet if needed) |              |             |    | Jet<br>Centrifugal  | Reciproc<br>Other   | ating 📡              |
| 8. Elevation:   | 19. Remarks:        |                  |              | I           |    | 20. Water well contractor's co  | ertification:   | eport "              |
| Topography:   |                     |                  |              |             |    | is true to the best of my knowl Minter Wilson Di                        | edge and belief.  | <u>208</u> ≨         |
| Hill Slope Upland   |                     |                  |              |             | _  | Business name Address Rdx A, Gard                                       | m C1 by, KS   | 67846                |
| Valley  |                     |                  |              |             |    | Authorized repre  | exerps of the   | 477- 1               |

M1-1023

1.3 X C. J.

## October 31, 1978

## Fairleigh Corp. Scott County

Static Water Level - 90

| 0   | 1   | Top Soil                                      |  |  |  |
|-----|-----|---|--|--|--|
| 1   | 4   | Clay  |  |  |  |
| 4   | 11  | Fine Sand                                     |  |  |  |
| 11  | 34  | Fine to med. sand and gravel (loose)          |  |  |  |
| 34  | 43  | Brown Clay                                    |  |  |  |
| 43  | 50  | Brown Clay Streaks of Gravel 30% (loose)      |  |  |  |
| 50  | 67  | Brown Clay                                    |  |  |  |
| 67  | 89  | Fine to med. sand and gravel 10% Clay (loose) |  |  |  |
| 39  | 130 | Brown Clay and White Rock (tight)             |  |  |  |
| 130 | 162 | Fine to med. sand and gravel (loose)          |  |  |  |
| ₹62 | 170 | Yellow Clay                                   |  |  |  |

T. D. 170