USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## MODOL SE WATER WELL RECORD KSA 820-1201-1215

## 20 33W 18 A

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)
Topeko, Konsos 66620

| County Fraction   | Section  | number   | Township number Range number   |
|---|--|----------|--|
| 1. Location of well:  Scott  No. 1/4 NE 1/4 NN 1/4                                  |  |          | T 20 S R 33 E  |
|   | vner of wel                                      |          | Norman Keyes   |
| et address of well location if in city:  Scott City, KS R.R. or street:             |  |          | RFD #2   |
| City, state, zip code:  |  |          | Scott City, KS 67871  6. Bore hole dia. 9 in. Completion date  |
| 4. Locate with "X" in section below:  Sketch map:                                   |  |          | Well depth 140 ft. 10-20-75  |
| 14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1  |  |          | 7 Cable tool X Rotary Driven Dug   |
|   |  |          | 8. Use: X_ Domestic Public supply Industry   |
|   |  |          | Irrigation Air conditioning Stack  |
| 1   sw   se   \/ 300'   |  |          | Lawn Oil field water Other 9. Casing: Material Plas_ Height: Above below                               |
| Egeddat   |  |          | Threaded WelderGlue Surface 12 in.   |
|   |  |          | RMP_X PVCWeight1_8 lbs./ft. Dia. 5 in. to 120t. depth Wall Thickness inches or                         |
| 5. Type and color of material   | From   | То       | Dia in. to ft. depth wall inchess anches or ft. depth gage No  |
| 7. Type and cold of material  |  |          | 10. Screen: Manufacturer's name  |
| Clay  | 0  | 47       | Type RMP Dia. 5 in.  |
| Rock  | 47   | 51       | Set between 120 ft. and 140 ft.  |
|   | <del>                                     </del> |          | ft. andft.   |
| Clay  | 51   | 55       | Gravel pack? <u>Yes</u> Size range of material $\frac{1}{2}$ -1/8                                      |
| Сур   | 55   | 68       | 11. Static water level: mo./day/yr.<br>97 ft. below land surface Date 10-20-75                         |
| Clay  | 68   | 77       | 12. Pumping level below land surfaces:   |
| Sd rock H   | 77   | 89       | 107 ft. after 1 hrs. pumping 10 g.p.m. ft. after hrs. pumping g.p.m.                                   |
|   |  |          | Estimated maximum yield  |
| Clay  | 89   | 92       | 13. Water sample submitted: mo./day/yr.  |
| Sd coarse Tight   | 92   | 115      | 14. Well head completion:  |
| Sdcoarse  | 115  | 138      | X Pitless adapter Inches above grade<br>15. Well grouted? Yes  |
| Clay yellow   | 138  | 140      | With:_X_ Negt cementBentonite Concrete   |
| Stay Jotton   | 1,00   | 1-70     | Depth: From U ft. to 15 ft.  |
| Shale   | 140  |          | 16. Negrest source of possible contamination: ft. 135 Direction Type Septic                            |
|   |  | <u> </u> | Well disinfected upon completion? Yes No   |
| BROCK 138'  |  |          | 17. Pump: Not installed   Manufacturer's ngme, Red Jacket  |
|   |  |          | Model number 50114 HP 2 Vols 30 Length of drop pipe 138 ft. capacity 10 g.p.m.                         |
|   | +  |          | Length of drop pipe 130 ft. capacity 10 g.p.m.  Type:  |
|   |  | -        | Submersible Turbine Reciprocating  |
| (Use a second sheet if needed)  |  |          | Centrifugal Other  |
| 18. Elevation: 19. Remarks: 2583 (TOPO)   |  |          | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report |
|   |  |          | is true to the best of my knowledge and belief.  |
|   |  |          | Weisharr Drilling 232  |
| Hill Slope  |  |          | Address Namas Ligans No. 1   |
| X Upland  |  |          | Signature Approximation 1 1 1 20-75  |
| Forward the white, blue and pink copies to the Department of Health and Environment |  |          | Forgy WWC-5  |