

1. LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>McPherson</u>	<u>NW 1/4 NE 1/4 NW 1/4</u>	<u>35</u>	T <u>20</u> S	R <u>5</u> E <u>(W)</u>

Distance and direction from nearest town or city street address of well if located within city?

9 mi. N of Medora

2. WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code :	

3. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
W	E
S	

4. DEPTH OF COMPLETED WELL 127 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 9-5-95Pump test data: Well water was 124 ft. after 4 hours pumping 3 gpmEst. Yield 3 gpm: Well water was 36 ft. after 5 1/2 hours pumping 127 gpmBore Hole Diameter 9 in. to 36 ft., and 5 1/2 in. to 127 ft.

WELL WATER TO BE USED AS:

<input checked="" type="checkbox"/> Domestic	<input type="checkbox"/> 3 Feedlot	<input type="checkbox"/> 6 Oil field water supply	<input type="checkbox"/> 9 Dewatering	<input type="checkbox"/> 12 Other (Specify below)
<input type="checkbox"/> 2 Irrigation	<input type="checkbox"/> 4 Industrial	<input type="checkbox"/> 7 Lawn and garden only	<input type="checkbox"/> 10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No X

5. TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
<input checked="" type="checkbox"/> PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 6 in. to 36 ft., Dia 12 in. to 160 lbs./ft. Wall thickness or gauge No. 160Casing height above land surface 12 in., weight

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	<input checked="" type="checkbox"/> 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	<input checked="" type="checkbox"/> 1 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 23 ft. to 31 ft., From 31 ft. to 127 ft.GRAVEL PACK INTERVALS: From 23 ft. to 31 ft., From 31 ft. to 127 ft.

6. GROUT MATERIAL:

1 Neat cement	2 Cement grout	3 Bentonite	4 Other
---------------	----------------	-------------	---------

Grout Intervals: From 23 ft. to 23 ft., From 31 ft. to 36 ft., From 36 ft. to 127 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	<input checked="" type="checkbox"/> 8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? S How many feet? 175

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	7	BK Soil		
7	30	Rocky Br Clay		
30	127	Shale		

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-5-95 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 9-23-95under the business name of Miller Drilling by (signature) Eg Mills

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.