


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: McPherson		SW 1/4 SE 1/4 SE 1/4	6	T 20 S	R 5 W
Distance and direction from nearest town or city street address of well if located within city? 3 miles south of Windom, KS					
2 WATER WELL OWNER: David Ekholm					
RR#, St. Address, Box #: Rt			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Windom, KS 67491			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 8-26-91			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10-15 gpm: Well water was 9.5 ft. after 1 1/2 hours pumping 6 gpm			
		Bore Hole Diameter: 8 in. to 13.5 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 100 ft. Dia 11.0 in. to 120 ft. Dia in. to ft.					
Casing height above land surface 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:					
From 100 ft. to 110 ft.		From ft. to ft.			
From 120 ft. to 130 ft.		From ft. to ft.			
GRAVEL PACK INTERVALS:					
From 25 ft. to 130 ft.		From ft. to ft.			
From ft. to ft.		From ft. to ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 5 ft. to 25 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination: None within 1/4 mile					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	7	Brown Clay			
7	14	Red Shale			
14	25	Gray Shale			
25	35	Red Shale			
35	50	Gray Shale			
50	60	Red Shale			
60	65	Hard Gray Shale			
65	85	Brown Shale			
85	110	Gray Shale			
110	125	Red Shale			
125	135	Gray Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-26-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 9-5-91 under the business name of Peterson Irrigation, Inc. by (signature) <i>Mike Peterson</i>					