


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County Mcpherson	Township name Hayes	Fraction NE 1/4 - NE 1/4	Section number 12	Town number T-20-S	Range number R 5-W																																															
Distance and direction from nearest town or city: 2 mi south			3 Owner of well: DALE YODER																																																		
Street address of well location if in city: 1- West of CONWAY			Address: RR #1 CONWAY, KANSAS																																																		
Locate with "X" in section below: N  W E S 1 Mile			Sketch map:			4 Well depth: 58 ft. Date of completion 5/19/75 Well diameter 10 in.																																															
<table border="1"><thead><tr><th>2</th><th>Type and color of material</th><th>From</th><th>To</th></tr></thead><tbody><tr><td></td><td>loam to clay</td><td>0</td><td>5</td></tr><tr><td></td><td>brown clay to grey shale</td><td>5</td><td>10</td></tr><tr><td></td><td>grey shale</td><td>10</td><td>23</td></tr><tr><td></td><td>brown shale (reddish cast)</td><td>23</td><td>25</td></tr><tr><td></td><td>grey-white shale</td><td>25</td><td>32</td></tr><tr><td></td><td>brown soft shale - w/ fault</td><td>32</td><td>39</td></tr><tr><td></td><td>hard dark grey shale</td><td>39</td><td>41</td></tr><tr><td></td><td>gray shale</td><td>41</td><td>45</td></tr><tr><td></td><td>gray - brown semi soft shale</td><td>45</td><td>48</td></tr><tr><td></td><td>brown shale soft - w/ fault</td><td>48</td><td>52</td></tr><tr><td></td><td>hard dark grey shale</td><td>52</td><td>58</td></tr></tbody></table>			2	Type and color of material	From	To		loam to clay	0	5		brown clay to grey shale	5	10		grey shale	10	23		brown shale (reddish cast)	23	25		grey-white shale	25	32		brown soft shale - w/ fault	32	39		hard dark grey shale	39	41		gray shale	41	45		gray - brown semi soft shale	45	48		brown shale soft - w/ fault	48	52		hard dark grey shale	52	58	5 <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
			2	Type and color of material	From	To																																															
				loam to clay	0	5																																															
				brown clay to grey shale	5	10																																															
				grey shale	10	23																																															
				brown shale (reddish cast)	23	25																																															
				grey-white shale	25	32																																															
				brown soft shale - w/ fault	32	39																																															
				hard dark grey shale	39	41																																															
				gray shale	41	45																																															
				gray - brown semi soft shale	45	48																																															
				brown shale soft - w/ fault	48	52																																															
	hard dark grey shale	52	58																																																		
6 Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well <input type="checkbox"/>																																																					
7 Casing: Material PVC Height: above/below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 18 in. Diam. 5" Weight 2.32 lbs./ft. + 18 in. to 58 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																					
8 Screen: Jet stream pipe Manufacturer OWN Type PVC Dia. 5" Slot/gauze .0468 Length 20' Set between 30 ft. and 40 ft. Fittings: 48 to 58 1/2 to 1 1/4" Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material																																																					
9 Static water level: 21 ft. below land surface Date 5/19/75																																																					
10 Pumping level below land surfaces: 23 ft. after 2 hrs. pumping 20 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.																																																					
11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date																																																					
12 Well head completion: <input checked="" type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade																																																					
13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From 15 ft. to 3 ft.																																																					
14 Nearest source of possible contamination: ft. 65' Direction NE Type house sewer line Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No																																																					
15 Pump: Manufacturer's name Aermator Model number SD12-30 HP 1/2 Volts 115 Length of drop pipe 50 ft. capacity 15 g.m.p. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																																					
16 Remarks: elevation Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley																																																					
17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. PAUL'S INC #175 Business name License No. Address Box 26 - Hesston Signed Paul B. Paul Date 5/19/75 Authorized representative																																																					