

1 LOCATION OF WATER WELL: County: Rice		Fraction NW 1/4 NE 1/4 SE 1/4	Section Number 29	Township Number T 20 S	Range Number R 7 EW
---	--	----------------------------------	----------------------	---------------------------	------------------------

Distance and direction from nearest town or city street address of well if located within city?
 1 mile East of Saxmon, 1/2 mile South, & 1/4 mile West

2 WATER WELL OWNER: American Salt Company RR#, St. Address, Box #: P.O. Box 498 City, State, ZIP Code: Lyons, Kansas 67554		Board of Agriculture, Division of Water Resources Application Number:
--	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 53 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1..... ft. 2..... ft. 3..... ft.
	WELL'S STATIC WATER LEVEL: 10'6" ft. below land surface measured on mo/day/yr May 7, 1985
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
X PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter: 4 in. to 58 ft., Dia				
Casing height above land surface: 18 in., weight				lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:		X PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	X Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From 42 ft. to 53 ft., From			
	From			
GRAVEL PACK INTERVALS:	From 10 ft. to 53 ft., From			
	From			

6 GROUT MATERIAL: X Neat cement		2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From				
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None
Direction from well?		How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Top Soil			
3	13	Clay			
13	44	Medium sand			
44	49	Clay			
49	53	Medium fine sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 7, 1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) May 7, 1985 under the business name of Rosencrantz & Bemis Enterprise by (signature) Mike Rosencrantz	
---	--

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.