

1 LOCATION OF WATER WELL: County: <u>Rice</u>	Fraction <u>SE 1/4 NE 1/4 NE 1/4</u>	Section Number <u>30</u>	Township Number <u>T 20 S</u>	Range Number <u>R 7 E/W</u>
--	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?  
 Approximately  $\frac{1}{2}$  mile north of Saxman

2 WATER WELL OWNER: Turner and Boisseau Chartered  
 RR#, St. Address, Box #: 3900 Broadway Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Great Bend, KS 67530 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: unknown

Depth(s) Groundwater Encountered 1. 10.76 ft. 2. 10-15-93 ft. 3. 10-15-93 ft.

WELL'S STATIC WATER LEVEL 10.76 ft. below land surface measured on mo/day/yr 10-15-93

Pump test data: Well water was not ch'd ft. after          hours pumping          gpm

Est. Yield unknown gpm: Well water was          ft. after          hours pumping          gpm

Bore Hole Diameter 6 1/2 in. to 69 ft., and          in. to          ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes          No X; If yes, mo/day/yr sample was submitted         

Water Well Disinfected? Yes          No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>        </u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>        </u>
		7 Fiberglass		Threaded <u>        </u>

Blank casing diameter 2 in. to 54 ft., Dia          in. to          ft., Dia          in. to          ft.

Casing height above land surface 24 in., weight 44 lbs./ft. Wall thickness or gauge No. .091

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify) <u>        </u>
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) <u>        </u>	

SCREEN-PERFORATED INTERVALS: From 54 ft. to 64 ft., From          ft. to          ft.

GRAVEL PACK INTERVALS: From 49 ft. to 69 ft., From          ft. to          ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug

Grout Intervals: From          ft. to          ft., From          ft. to          ft., From 0 ft. to 49 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below) <u>        </u>
			13 Insecticide storage	None known <u>        </u>

Direction from well?          How many feet?         

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	5	Clay, brown, hard, silty			
5	9	Clay, tan, hard, silty			
9	11	Clay, brown, hard, silty			
11	30	Sand and gravel, fine, medium, loose, clean			
30	35	Sand, fine, medium, loose, clean			
35	64	Sand and gravel, fine, medium, loose, clean			
64	69	Shale, red, hard			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-15-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185. This Water Well Record was completed on (mo/day/yr) 10-21-93 under the business name of Clarke Well & Equipment, Inc. by (signature)