

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

Blank box for application number

1 LOCATION OF WATER WELL: County: Rice, Fraction NW 1/4 NE 1/4 NE 1/4 SE 1/4, Section Number 14, Township No. T 20 S, Range Number R 8, Global Positioning System (GPS) information: Latitude: .38,31,128, Longitude: 098,16699, Elevation: 1617, Datum: WGS 84, NAD 83, NAD 27, Collection Method: GPS unit, Digital Map/Photo, Topographic Map, Land Survey, Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m

2 WATER WELL OWNER: North American Salt, RR#, Street Address, Box #: 1662 Avenue N, City, State, ZIP Code : Lyons, Kansas 67554, 3 LOCATE WELL WITH AN "X" IN SECTION BOX: Diagram showing section box with 'X' in SE, 4 DEPTH OF COMPLETED WELL 60, Depth(s) Groundwater Encountered (1) 12, (2) 12, (3) 12, WELL'S STATIC WATER LEVEL 12, Pump test data: Well water was 7.7/8 ft. after 12 hours pumping, EST. YIELD 7.7/8 gpm, Bore Hole Diameter 7.7/8 in. to 12 in. to 12 in. to 12 in. to, WELL WATER TO BE USED AS: Public water supply, Geothermal, Injection well, Domestic, Feedlot, Oil field water supply, Dewatering, Other (Specify below), Irrigation, Industrial, Domestic-lawn & garden, Monitoring well, Was a chemical/bacteriological sample submitted to Department? Yes No, If yes, mo/day/yr sample was submitted, Water well disinfected? Yes No

5 TYPE OF CASING USED: Steel PVC Other, CASING JOINTS: Glued Clamped Welded Threaded, Casing diameter 4 in. to 50 ft., Diameter in. to in. to in. to in. to, Casing height above land surface 24 in., Weight 160 lbs./ft., Wall thickness or gauge No. 173, TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify), SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole), Louvered shutter Key punched Wire wrapped Saw cut Other (specify), SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From ft. to ft., From ft. to ft., GRAVEL PACK INTERVALS: From 60 ft. to 45 ft., From 40 ft. to 20 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other, Grout Intervals: From 45 ft. to 20 ft., From 20 ft. to 0 ft., From ft. to ft., What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below), Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well plugged monitor well, Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well, Direction from well west, Distance from well 10

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-2 Top Soil, 2-13 Clay, 13-60 Medium Sand and Gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 12-30-09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 12-31-09 under the business name of Rosencrantz-Bemis Ent. by (signature) Susan Dodson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.