KOLAR Document ID: 1534255

WATER		ECORD Correction		WWC-5 e in Well Use			sion of Wate urces App. N			Well ID		
		ATER WEL		Fraction			tion Numbe		Township Numbe		ge Number	
County:					1/4 1/4					R	$\Box E \Box W$	
Business: d Address: Address:						treet or Rural Address where well is located (if unknown, distance and irection from nearest town or intersection): If at owner's address, check here:						
City:			State:	ZIP:								
3 LOCATE WITH "X	IPLETED WELL :							(decimal degrees)				
SECTION		Depth(s) Groundwater Encountered: 1)					Longitude:					
Ν		2) ft. 3) ft., or 4) D D WELL'S STATIC WATER LEVEL:					l Datum: ☐ WGS 84 ☐ NAD 83 ☐ NAD 27 Source for Latitude/Longitude:					
			below land surface, measured on (mo-day-yr)						unit make/model:)	
NW	- NE	above land surface, measured on (mo-day-yr).					(WAAS enabled? Yes No)					
		Pump test data: Well water was ft. after hours pumping gpm					\Box Land Survey \Box Topographic Map					
W	E	Well water was ft.					Online Mapper:					
				ours pumping gpm								
		Estimated Yield:gpm					6 Elevation :ft. □ Ground Level □ TOC <u>Source</u> : □ Land Survey □ GPS □ Topographic Map					
S	le	Bore Hole Diameter: in. to f										
7 WELL WATER TO BE USED AS:												
1. Domestic: 5.												
☐ Househo □ Lawn &		6. Dewatering: how many wells?										
\Box Lawn α		7. Aquifer Recharge: well ID				Cased Uncased Geotechnical 12. Geothermal: how many bores?						
	ε				ediation: well ID			a) Closed Loop 🗌 Horizontal 🗌 Vertical				
3. ☐ Feedlot				-			b) Open Loop Surface Discharge Inj. of Water					
4. Industrial Recovery Injection 13. Other (specify):												
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
Steel Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)												
	□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From											
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft. o ft. o ft. o ft.												
Grout Intervals: From ft. to ft., From ft. to ft. from ft. to ft.												
Nearest source		e contaminati	o n: No Lateral Line	potential source of co s ☐ Pit Privy			nin 200 ft. Livestock Pe		☐ Insectic	ida Staraga		
Septie 1			Cess Pool	\square Fit Fit vy \square Sewage I			Fuel Storage					
□ Watertig	ht Sewer Lir	nes 🗆 S	leepage Pit	☐ Feedyard			Fertilizer Sto					
Direction from well? ft.												
10 FROM	TO		ITHOLOG		FRC		TO		HO. LOG (cont.) or	PLUGGIN	GINTERVALS	
							-					
					Note	s:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, a reconstructed, or plugged												
under my jur	risdiction ar	id was compl	eted on (n	no-day-year)		and t	his record	is tru	ie to the best of my	y knowleds	ge and belief.	
				no-day-year) 								
under the business name of Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.												
	KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
Visit us at htt	p://www.kdhe	ks.gov/waterwel	/index.html							KS	A 82a-1212	