

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Rice	Fraction NW 1/4 NE 1/4 SE 1/4	Section number 9	Township number T 20 S R 8	Range number 8
2. Distance and direction from nearest town or city: 1/2 mile south of Lyons, KS Street address of well location if in city:			3. Owner of well: Cecil Miller etal * R.R. or street: Route 1 City, state, zip code: Lyons, KS 67554		
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile			Sketch map: Test Well No. 6 1000'W & 2570'N - SE Cor. 9		
5. Type and color of material			From	To	
Top Soil			0	3	
Brown and Gray Clay			3	22	
Sand and Gravel			22	30	
Gray Clay			30	37	
Sand and Gravel			37	42	
Gray and Yellow Clay			42	50	
Sand and Gravel			50	71	
Red Shale			71	75	
(Use a second sheet if needed)					
18. Elevation: (Ground) 1657.9 Topography: ___ Hill ___ Slope ___ Upland ___ Valley		19. Remarks: * Work performed on behalf of Cecil Miller etal to obtain ground water information RE: Miller vs. Cudahay lawsuit. **Test wells were considered temporary when drilled. Due to pending litigations, a decision to plug wells or grout and establish permanent observation wells has not been made.			
		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Clarke Well & Equip., Inc. 185 Business name Great Bend, KS 67530 License No. Address 8-25-78 Signed [Signature] Date 12/13/77 Authorized representative			

6. Bore hole dia. 5 in. Completion date 12/13/77
Well depth 70 ft.

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other - **Test Well**

9. Casing: Material PVC Height: Above or below
Threaded Welded Surface 1.60
RMP PVC Weight .631 lbs./ft.
Dia. 2 1/2 in. to 60 ft. depth Wall Thickness: inches or
Dia. in. to ft. depth gage No. .110

10. Screen: Manufacturer's name Clarke
Type PVC Dia. 2 1/2"
Slot/gauze 1/8" Length 10'
Set between 60 ft. and 70 ft.
 ft. and ft.
Gravel pack? yes Size range of material 1/4"

11. Static water level: 18 mo./day/yr.
18 ft. below land surface Date 3-17-78

12. Pumping level below land surfaces: NC
 ft. after hrs. pumping g.p.m.
 ft. after hrs. pumping g.p.m.
Estimated maximum yield g.p.m.

13. Water sample submitted: Chl. 182 mo./day/yr.
 Yes No Date 12/13-77

14. Well head completion:
 Pitless adapter Inches above grade

15. Well grouted? No **
With: Neat cement Bentonite Concrete
Depth: From ft. to ft.

16. Nearest source of possible contamination:
ft. Direction Type
Well disinfected upon completion? Yes No

17. Pump: Not installed
Manufacturer's name
Model number HP Volts
Length of drop pipe ft. capacity g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

T 20 S R 8 W E 9 N W I S E 1/4 1/4 8 1/4