


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Rice	Fraction SW 1/4 NW 1/4 SE 1/4	Section number 21	Township number T 20S	Range number S R 8W E/W
2. Distance and direction from nearest town or city: Street address of well location if in city: 4 mi. south of Lyons, 1 1/2 West, 1/4 North in field			3. Owner of well: R.R. or street: Steve Sellers Lyons, Kansas 67554 City, state, zip code:		
4. Locate with "X" in section below: N 1 Mile W E S 1 Mile			Sketch map: 		
5. Type and color of material			From	To	6. Bore hole dia. 26 in. Completion date 6/29/79 Well depth 65 ft.
Top soil			0	3	7. <input type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
Brown clay			3	9	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other
Med. sand, loose, took water			9	38	9. Casing: Material Transite Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC 1/1 Weight 160 lbs./ft. Dia. 16 in. to 0 ft. depth Wall Thickness: inches or Dia. 16 in. to 39 ft. depth gage No. 311.237
Clay			38	43	10. Screen: Manufacturer's name Johnson Type sawed Dia. 16 Slot/gauze 3/16 Length 26 Set between 39 ft. and 65 ft. ft. and _____ ft.
Med. sand, fairly loose, took water			43	67	11. Static water level: _____ mo./day/yr. 18 ft. below land surface Date 6/29/79
Clay			67	135	12. Pumping level below land surfaces: 950 g.p.m. 32 ft. after 1 hrs. pumping 43 ft. after 2 hrs. pumping 800 g.p.m. Estimated maximum yield 950 g.p.m.
					13. Water sample submitted: _____ mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____
					14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade
					15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
					16. Nearest source of possible contamination: ft. _____ Direction None Type _____ Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No
					17. Pump: _____ Not installed Manufacturer's name Western Land Roller Model number 2 Stage DC # 30 Volts _____ Length of drop pipe 300 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation:			19. Remarks: Drilled Irr. well & cased well at 65'		
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Rosencrantz-Bemis Ent. Inc. 134 Business name License No. Address 1211 W. 4th Hutchinson, Ks. Signed Mike Rowe Date 8/2/79 Authorized representative		

Flow

20
 21
 SW 1/4 SE
 1/4 1/4 SW SE